

The STEYR KOMPAKT S from 55 hp to 75 hp

FARM WORK MADE **EASY**



Your partner to rely on.

STEYR
TRAKTOREN

AS **MULTI-FACETED** AS THE WORK YOU DO



The KOMPAKT S class from STEYR is revolutionising the cost-benefit calculation process. The models are light, manoeuvrable and flexible. Equipped with the proven technology of its larger brethren, these models are ideally suited to virtually all kinds of application. The unique manoeuvrability of the KOMPAKT S class makes it the perfect working implement for front-loader operations in animal sheds and around the farmyard. Whether involved in agriculture or forestry, commercial or municipal operations, with a STEYR KOMPAKT S you have the most versatile vehicle with the greatest number of benefits on the market in exchange for modest investment and operating costs.



The art of maximum comfort

The spacious 'Comfort' cab with a level cab floor is standard on all KOMPAKT S tractors. The optimised ergonomic arrangement of control elements enables vehicle and hydraulic and PTO functions to be operated intuitively and safely. The greatly enhanced acoustic insulation reduces the noise level in the cab. The perfect all-round visibility on all sides guarantees that implements can be connected up safely. The integral high-view window also provides a clear view of the front loader, even when it is fully raised.



Great performance

The common-rail turbodiesel engines produce optimum power combined with enhanced fuel economy. Tried and tested transmission variants, optionally with creeper gears and Powershuttle, as well as with electrohydraulically engageable all-wheel drive, deliver power to the wheels in an efficient and carefully applied manner. This always leaves sufficient power for the PTO to complete every step of an operation rapidly.



Robust hydraulics

With the powerful rear hitch and the power-efficient mechanical (MHR) or Electronic Hitch Regulation (EHR), the KOMPAKT S can carry loads up to 2,500 kg.



Engine

The FPT F5C 4-cylinder common-rail engine not only delivers its power at nominal speed, but starts doing so right from the fuel-saving level of 1,800 rpm. This not only helps to keep fuel consumption low while hard at work, but also enhances ride comfort because it keeps noise and vibration levels relatively low too.



Remarkably manoeuvrable and safe

With a turning radius of just 3.82 m you can save a great deal of time in the farmyard, in buildings and at headlands. Even when the tractor is heavily laden, the wet disc brakes deliver plenty of braking power. The electrohydraulic actuation which engages the all-wheel drive and the differential locks is controlled at the right-hand side of the driver console.

MODEL		4055 KOMPAKT S	4065 KOMPAKT S	4075 KOMPAKT S
TRANSMISSION				
Synchromesh transmission with 4 gears in 3 groups 12 forward and 12 reverse gears 40 km/h	With shuttle shift / With Powershuttle	● / ●	● / ●	● / ●
Creeper transmission with 20 forwards and 20 reverse gears	With shuttle shift / With Powershuttle	● / ●	● / ●	● / ●
ENGINE				
Rated engine power ECE R120 ¹⁾ [kW/hp]		43 / 58	48 / 65	55 / 75
Common Rail turbodiesel with intercooler / stage IIIB	Rated engine speed [rpm]	2,300	2,300	2,300
	Max. torque ECE R120 ¹⁾ [Nm @ rpm]	265 @ 1,300	290 @ 1,300	320 @ 1,300
	OECD torque increase [%]	48	46	40
	Number of cylinders / capacity [cm ³]	4 / 3,400	4 / 3,400	4 / 3,400
	Fuel tank capacity [litres]	90	90	90
POWER TAKE-OFF				
PTO speed @ engine [rpm]	540/540E	1,958 / 1,592	–	–
Stationary PTO		●	●	●
HYDRAULICS				
MHR Mechanical hitch control		●	●	●
Max. displacement of tandem pump hydraulics/steering [L/min]		48 / 36	48 / 36	48 / 36
Max. lifting force / continuous lifting force acc. to OECD at 610 mm [kg]		2,500 / 2,100	2,500 / 2,100	2,500 / 2,100
Max. number of auxiliary control units rear mounted centrally mounted		3 / 2	3 / 2	3 / 2
ALL-WHEEL DRIVE STEERING				
Electrohydraulic all-wheel drive engagement		●	●	●
Steering lock [°]	Min. turning radius [m]	55° / 3.66	55° / 3.66	55° / 3.66
TYRES²⁾				
Standard tyres*	Front / Rear	14.9R20 / 16.9R30	14.9R20 / 16.9R30	14.9R20 / 16.9R30
WEIGHTS* with cab and all-wheel drive				
Unladen weight [kg]	Permitted gross vehicle weight [kg]	2,280 / 4,500	2,280 / 4,500	2,280 / 4,500
CAB				
Spacious cab with wide entry door, individually adjustable driver's seat with lumbar support, minimum vibration, max. noise level 75 dB(A), heating and air-conditioning systems, wide windscreen and great all-round visibility exhaust pipe up beside the A-pillar, tapered bonnet, high visibility roof, powerful headlight package, ergonomically configured controls, tractor monitor.				

● Standard ● Optional – Not available

* Depending on country-specific regulations and specifications

¹⁾ ECE R120 complies with ISO 14396 and 97/68/EC

²⁾ Other tyres available as Special Equipment on request (i.e. as cost options)

You drive better when you are safe. Before using this vehicle, please read the Operating Manual and become familiar with the use of each of the controls. Note the contents of the instruction panels and use the safety equipment for your own personal safety. This brochure is intended for use internationally. The availability of a few models and of standard and special equipment items may vary from one country to another.

STEYR reserves the right at any time and without prior announcement to make changes to the design and technical version without this in any way obliging STEYR to transfer these to units already sold. Details, descriptions and pictorial material reflect the current status at the date of publication, but can be amended without prior announcement and at any time. Pictorial materials may show certain national versions, items of special equipment as well as non-complete standard versions.

TP01 / SM / 10.23 / Printed in Austria – Cod. n. 23S0004COMINB
www.steyr-traktoren.com

