

VESTRUM®

SPECIFICATIONS



VESTRUM SPECIFICATIONS

CASE IH

CASE IH

| MODEL | VESTRUM 100 | VESTRUM 110 | VESTRUM 120 | VESTRUM 130 |
|--|--|-------------|-------------|-------------|
| Operator Station | Cab only | | | |
| Traction | MFD only | | | |
| ENGINE | | | | |
| Type | Tier 4 B/Final - Stage V with 4 cylinder, turbocharged 4.5L FPT | | | |
| Displacement | 273 cu. in. | | | |
| Engine HP* | 100 | 110 | 120 | 130 |
| PTO HP* | 76 | 88 | 102 | 111 |
| Emissions Treatment | Selective Catalytic Reduction (SCR) | | | |
| Number of Valves | 16 | | | |
| Alternator | 200 amp | | | |
| Battery | 12 volt – 176 Ah 1300 EN CCA | | | |
| TRANSMISSION/PTO | | | | |
| Option (A) | 24×24 ActiveDrive 8 dual-clutch transmission 25 mph (40 kph) | | | |
| Option (B) | CVXDrive CVT transmission 25 mph (40 kph) | | | |
| Creeper | Optional on ActiveDrive 8 transmission | | | |
| PTO | 540/540E/1,000 rpm interchangeable PTO shaft | | | |
| AXLES | | | | |
| Front | Class 1.75 front axle with electro hydraulic differential lock | | | |
| Rear | Flange | | | |
| HYDRAULICS/HITCH | | | | |
| Type | Closed center load sensing pump | | | |
| Rear Remotes (Standard/Optional) | 2 mechanical + 1 electronic / 2 mechanical + 2 electronic, 3 or 4 electronic | | | |
| Hydraulic Pump/Flow | 28.5 gal./min. (108 L/min) | | | |
| 3-Point Hitch Category (Standard/Optional) | EDC with lower link sensing / Cat 2 flex link ends | | | |
| Standard Lift Capacity | 6,700 lb. (3,039 kg) lift capacity with dual 80 mm external rams | | | |
| CAPACITIES | | | | |
| Fuel Tank | 47 gal. (180 L) | | | |
| Diesel Exhaust Fluid Tank | 5 gal. (19 L) | | | |
| DIMENSIONS & WEIGHTS | | | | |
| Wheelbase | 98.1 in. (2,490 mm) | | | |
| Overall Length to End of Lower Links | 173.1 in. (4,397 mm) | | | |
| Overall Height | 111.70 in. (2,835 mm) | | | |
| Tractor Weight | 12,900 lb. (5,851 kg) | | | |

*at 2,200 ERPM rated engine speed

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2023 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH23092501

