

FARMALL C

TRACTORS 101 & 117 HP



THE ONE FOR ALL

The new FARMALL C series shows our commitment to our heritage and continuing our legacy within this power segment. Ready for the future by honouring the past.

82 l/min

Hydraulic flow

7 tonne
GVW

FARMALL C

2 models 101 hp and 117 hp

The new Farmall C is the most comfortable and versatile utility tractor, delivering high performance with driving pleasure. To meet modern farming demands, we enhanced the Farmall C with a new style, improved visibility, and wide offering of LED lighting packages. The ActiveDrive 2, 24 x 24 Hi-Lo transmission offers great versatility and improved operator experience. Upgrade to the latest standard of Case IH precision technology same as the top of the line up.

THE EFFICIENT ONE

- Increased GVW to 7 tonnes (+7.5%) with improved lifting capacity of 4.7 tonnes, enhancing daily task capabilities and versatility.
- More hydraulic flow up to 82 L/min, enabling operation of advanced implements and boosting reaction times.
- ActiveClutch simplifies operations with automatic clutch engagement when braking, reducing operator stress and enhancing safety, especially with front loaders.
- Heavy Duty front axle, equipped with larger cylinders for improved durability and steering capacity.
- Extended workhours thanks to increased fuel-tank capacity (130 L).

THE COMFORTABLE ONE

- Optional integrated cab suspension ensures a smooth ride, reducing operator fatigue.
- Upgraded joystick for simple, safe one-handed operation, featuring an improved shuttle switch, 3rd hydraulic function, engine speed memory, and gear shift.
- New display shows essential machine parameters and settings, keeping you informed without distractions for better focus on tasks.
- Enhanced LED lighting package provides superior visibility at night.
- Improved visibility due to repositioned exhaust offering an open, unobstructed view.
- Optional Variable Ratio Steering reduces steering wheel turns, enhancing driving comfort during extensive manoeuvring.



Improved
Visibility

Complete
digital
layout



Scan for more
information!

THE ALL-PURPOSE ONE

- ActiveDrive 2 transmission with 24x24 speed (40x40 with optional creeper) for improved speed adaption to the desired operation, improved power curve balance optimising handling experience.
- Larger tyre offering possible up to 540/65R38, improving traction while reducing compaction due to the larger footprint, boosting soil life.
- Front hitch with new wet clutch PTO offers increased power transfer and durability, enhancing serviceability.
- Auto-PTO (rear) stops the PTO at a preset lift arm height, improving operator comfort and supported within Headland Management.

THE ADVANCED ONE

- Full ISOBUS Class II capability available for integration of all ISOBUS implements into the cab's display.
- Optional Base Telematics with lifetime subscription including Instant access through Case IH FieldOps™ via your computer or App to the most important data like: main tractor parameters (fuel usage, performance, etc.) alerts, seasonal data or connected machine data.
- Case IH FieldOps Farming portal to provide a unified web and mobile experience.
- Optional Advanced telematics with Guidance Package available, which includes the Case IH Pro 1200, for agronomic data sharing, remote service support and lifetime subscription.

SPECIFICATIONS		FARMALL 100C	FARMALL 120C	
Operator Station		Cab		
ENGINE				
Type		4-cylinder, Stage V, FPT turbocharged & aftercooled.		
Displacement		3.6 L		
Engine HP*	101		117	
PTO HP*	85		100	
Rated Engine RPM		2,300		
TRANSMISSION - ELECTRONIC POWER SHUTTLE				
Standard		24 x 24 Hi-Lo (brake to clutch)		
Optional		40 x 40 Power Shuttle (brake to clutch w/ creeper)		
Differential Lock		Electrohydraulic		
FWD Engagement		Electrohydraulic		
PTO Speed		540/540E/1000		
AXLES				
Front (Standard / Optional)		Class 1.5 HD / Class 1	Class 1.5 HD	
Rear		Flange		
HYDRAULICS / HITCH				
Type		Open centre		
Rear Remotes (Standard / Optional)		2 / 3 or 3 + 01 Diverters		
Implement Pump Flow (Optional)		82.1 L		
3pt Hitch Category and Draft Sensing Type		Cat 2 EDC		
Lower Link End / Stabiliser Type		Flex ends / Telescopic stabilisers		
Lift Capacity @ BE		4700 kg		
CAPACITIES				
Fuel Tank		130 L		
Diesel Exhaust Fluid Tank		16 L		
DIMENSIONS & WEIGHT				
Wheelbase		2,350 mm		
Overall Length		4,020 mm		
Overall Height (Min / Max)^		2527 mm / 2736 mm		
Weight w/o Ballast (Cab only)		4,645 kg		

*At rated engine RPM. PTO horse power on Hi-Lo pending OECD test result. ^Heights are wheel dependent. Heights are to top of roof. No beacon or GPS antenna included.



SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial Australia Pty Ltd reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2025 CNH Industrial Australia Pty Ltd. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial Australia Pty Ltd, are the property of those respective companies. Printed in Australia. www.caseih.com

25CIHFARMALLCB

