





9F+3R Side shift gear box



ADDC Hydraulics with 750 kg Lift Capacity



28 inch (0.71 m) Track Width option









USAGE IN VARIOUS APPLICATIONS







Spraver PTO RPM 2000 540

Electrostatic Sprayer

L2/M1 2600 540

Gear | ERPM | PTO RPM | Intercultivation | Gear | ERPM | PTO RPM with Rotavator

L2 2600







Rotavator Gear **ERPM** PTO RPM Puddling L1/L2 2600



Gear ERPM PTO RPM 2600



Cultivator **ERPM** Gear H1/M2 1300-1500



Gear 1400-1600



Seed Drill Gear 1200-1300

ENGINE

No. of Cylinder / Displacement (CC) Engine Power (hp)

3 / 1318

29 (21.62 kW) @2800 ERPM

Dry type with Clogging sensor

TRANSMISSION

Max Torque (Nm)

Air Cleaner

Clutch Single - Diaphragm

9 Forward + 3 Reverse, Side Shift Transmission

Speed (Forward) - kmph 1.86 - 25.17 Speed (Reverse) - kmph 2.68 - 10.38 Differential Lock (Standard) Yes

BRAKES

Type Oil Immersed Disc Brakes

STEERING

Power Steering Type

PT₀

PTO RPM 540 & 1000

HYDRAULIC

Type **Automatic Depth & Draft Control**

Lifting capacity (kg) 750

TYRES

Front 180/85D12 / 5.00*12 (Narrow Track) Rear 8.3*20 / 8.00*18 (Narrow Track)

Turning Radius (m) 2.4

DIMENSIONS

Tractor Weight (kg) 920 Wheel Base (mm) 1490

Overall Width Minimum (mm) 1040 / 930 (Narrow Track)

Driver Seat Height Minimum (mm)

950

Note: Recommended Gear and ERPM may change as per soil condition and implement size.

CNH Industrial (India) Private Limited

Ridger

Plot No. 03, Udyog Kendra, Greater Noida - 201306, District Gautam Budh Nagar, Uttar Pradesh

Note: The specifications given above may be changed without any prior notice. For latest information, contact your nearest dealership. 2022 © CNH Industrial (India) Private Limited, all rights reserved.

Authorised Dealer