

FARMLIFT

TELESCOPIC LOADER MAX. LIFT HEIGHT FROM
6.1 – 9.1 m



DESIGNED FOR HANDLING EFFICIENCY

The all new Farmlift

160 l/min
Max. pump flow rate

360°
all-round visibility

Case IH continues its tradition of meeting the diverse needs of farms with the new generation of Farmlift telescopic loaders. These machines, ranging from 3,300 to 4,200 kg lift capacities and reaching up to 9.1 m, embody the ruggedness, reliability, and comfort synonymous with Case IH.

With enhanced styling, including new exterior design elements, and a complete new cab interior, they offer a fresh and modern look. Featuring a new 7 inch display and ergonomic controls on the armrest, they provide improved functionality. Equipped with smart hydraulic features and a 160 l/min CCLS pump, they deliver optimal performance.

NEW STYLING AND VISIBILITY

- New bonnet design
- 9 % better visibility to the right-hand side
- Excellent 360° visibility all-round
- High visibility roof ensures a perfect view of the loader

SMART HYDRAULIC FEATURES

- Bucket shaking function
- Return to position
- Adjustable boom responsiveness

AFS CONNECT TELEMATICS

- Manage your machine data and fleet
- Proactive business decisions thanks to real time notifications
- 1, 3 or 5 years available

MAXIMUM STABILITY

- Low centre of gravity
- Rear mounted boom acts as counter balance
- Longer wheelbase of 3 m



146 hp
max. power

EASY MAINTENANCE

- Extended engine service interval (1,000 hours)
- Unique compact Hi-eSCR2 exhaust gas aftertreatment system “for life” with no maintenance needed
- One piece bonnet and side panels allow easy access to the entire engine bay
- Fold-out radiators for easy cleaning

Models	Lift capacity [tons]	Max. reach [m]	Rated engine power [kW/hp (CV)]	Maximum engine power [kW/hp (CV)]	Transmission	Max. pump flow rate Standard (Optional) [l/min]
Farmlift 935	3.5	9.1	89 / 121	98 / 133	6x3 Autoshift	140 (-)
Farmlift 742	4.2	7.0	96 / 129	107 / 146	6x3 Autoshift	140 (160)
Farmlift 737	3.7	7.0	89 / 121	98 / 133	6x3 Autoshift	140 (-)
Farmlift 636	3.6	6.1	96 / 129	107 / 146	6x3 Autoshift	140 (160)
Farmlift 633	3.3	6.1	89 / 121	98 / 133	6x3 Autoshift	140 (-)



   
caseih.com

 Free phone: 00 800 22 73 44 00

Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **AKCELA** lubricants.

TP01 / SM / 11.23 / Printed in Austria - Cod.No. 23C4003COMINB

CASE IH