



A NEW ICON OF STYLE & TECHNOLOGY

NEW
4510 EXCEL
Drive The Future >>>

45 HP

33.55 kW



Also available in 2WD



Maximum Useful Power in Category



Eptaa PTO & Independent PTO Lever*



Paddy Specialty: Double Metal Face Sealing



8F+8R Synchro Shuttle*



Straight Axle Planetary Drive

*Optional

EXCEL SERIES

Model	Excel 4510 2WD	Excel 4510 4WD	
ENGINE	Engine Model	T-III A, S 325.5	T-III A, S 325.5
	Engine Type	Naturally Aspirated	Naturally Aspirated
	Engine Power	33.83 kW (45 hp)	33.83 kW (45 hp)
	Rated RPM	2200	2200
AIR CLEANER	Air Cleaner Type	DRY Air Cleaner with Clogging Sensor	DRY Air Cleaner with Clogging Sensor
TRANSMISSION	Clutch	Single Clutch/Double Clutch with IPTO Lever*	Double Clutch with IPTO Lever/ Single Clutch*
	Type	Constant Mesh AFD Side Shift	Constant Mesh AFD Side Shift
	Gear Box	8F+2R & 8F+8R*	8F+2R & 8F+8R*
PTO	PTO Type	Eptraa PTO - 540S, 540E*, Reverse PTO & GSPTO	Eptraa PTO - 540S, 540E*, Reverse PTO & GSPTO
	PTO HP	41	41
HYDRAULICS	Lift Capacity	1800 kg with Lift-O-Matic Hydraulic	1800 kg with Lift-O-Matic Hydraulic
	Lift-O-Matic	Yes	Yes
REAR AXLE	Type	Straight Axle Planetary Drive	Straight Axle Planetary Drive
BRAKES	Type	Oil Immersed Multi Disc Brake	Oil Immersed Multi Disc Brake
STEERING	Type	Power Steering	Power Steering
TYRE	Front	6.0-16	STS Axle - 8.0-18
	Rear	13.6-28	13.6-28
ELECTRICALS	Battery and Alternator Capacity	75 Ah & 35 Amp	75 Ah & 35 Amp
DIMENSIONS	Overall Length (mm)		3490
	Width (mm)		1780
	Height (mm)		2325
	Wheelbase (mm)	1900	2000
	Ground Clearance (mm)	395	360
	Weight (kg)*	1873	2150
FUEL TANK	Fuel Tank Capacity (L)	60	60
ADDITIONAL FEATURES	Heavy Duty Front Axle Support, Softek Clutch, Multisensing with DRC Valve, Tipping Trailer Pipe, Neutral Safety Switch, Clutch Safety Lock, Antiglare Rear View Mirror, Semi Flat Platform	Heavy Duty Front Axle Support, Multisensing with DRC Valve, Tipping Trailer Pipe, Neutral Safety Switch, Clutch Safety Lock, Antiglare Rear View Mirror, Semi Flat Platform	Heavy Duty Front Axle Support, Multisensing with DRC Valve, Tipping Trailer Pipe, Neutral Safety Switch, Clutch Safety Lock, Antiglare Rear View Mirror, Semi Flat Platform
OPTIONAL FEATURES	Synchro Shuttle 8F+8R, Double Clutch with IPTO Lever, Remote Valve, Paddy Special - Double Metal Face Sealing	Synchro Shuttle 8F+8R, Remote Valve, Double Clutch with IPTO Lever, Paddy Special - Double Metal Face Sealing	Synchro Shuttle 8F+8R, Remote Valve, Double Clutch with IPTO Lever, Paddy Special - Double Metal Face Sealing



Maximum Useful Power in Category

Powerful tractor, suitable for all heavy works




Eptraa PTO & Independent PTO Lever*

India's first tractor with 7 type of PTO speeds: Convenient for all PTO applications, longer clutch life



Paddy Specialty: Double Metal Face Sealing

Water proof transmission which allows deep puddling



8F+8R Synchro Shuttle*

Quick forward and reverse movement: Increases productivity



Straight Axle Planetary Drive

Power of 3 gears, transmits high power & torque: Less maintenance



Maximum Road Speed 33.3 km/hr

Maximum no. of trips in a day: Saves time & earn more money

*Optional #With bumper & rear weight

CNH INDUSTRIAL (INDIA) PVT. LTD.

Plot No. 03, Udyog Kendra, Greater Noida, District Gautam Budh Nagar, Uttar Pradesh.

Authorised Dealer

TOLL-FREE NO.
1800-419-0124
www.newholland.com/in

Note: New Holland believes in constantly working to bring improvements in their products. Therefore, the specifications given above may be changed without any prior notice. For latest information, contact your nearest dealership. The specifications given above are taken from the sub-clause of CFMTTI, Budni, Report/manufacturer's website/product leaflet.