

EUROPEAN







Clear Lens Headlamps with DRL Signature Lights



Side Silencer for clear front visibility



Increased Platform Height with Double Footstep & Heatguards

Model		NH 3600-2 Allrounder + (2WD) NH 3600-2 Allrounder + (4WD)	
ENGINE	Engine Model	FPT S8000 series	
	Engine Type	4 Stroke Natural Aspirated Engine	
	Engine Power	36.94 kW (50 HP Cat.)	
	Rated RPM	2100	
CLEANER	Air Cleaner Type	Oil Bath Type with Pre-Cleaner	
	Clutch	Double Clutch with Independent Clutch Lever	
NO	Gear Box	8F+2R / 12F+3R Creeper* / 12F+3R UG*	
11SSIS	Gear Box Type	Fully Constant Mesh / Partial Synchromesh*	
TRANSMISSISON	Speed Range, Kmph	Forward- 1.87 Kmph - 33.83 Kmph Reverse- 2.71 – 15.16 Kmph	Forward- 1.78 Kmph - 32.19 Kmph Reverse- 2.58 – 14.43 Kmph
	Min. Creeper Speed , Kmph	0.9 Kmph	
PTO	Туре	Independent, 6 Spline 540Std & GS PTO and Rev PTO (Optional)	
	RPM	540 @ 1800 ERPM	
HYDR- AULICS	Maximum Lift Capacity	ADDC Hydraulic Lift 1700 Kg Std, 2000 Kg with Assist Ram*	
	3 Point Linkage	Cat-II	
REAR AXLE	Туре	Hub-Reduction	
BRAKE	Туре	Real Oil Immersed Multi Disk Brake	
ING -	Туре	Power Steering	
TYRE	Front	6.5-16 / 7.5-16	9.5-24
	Rear	14.9-28	14.9-28
ELECTRIC- ALS	Battery and Alternator Capacity	88 Ah Battery & 45 Amp Alternator	
WEIGHT & DIMENSIONS	Overall Length (mm)	3465	3440
	Width (mm)	1815	1840
	Height (mm)	2390	2430
	Wheelbase (mm)	2040	1920
	Ground Clearance (mm)	445	390
	Weight (kg)	2100 kg	2460 kg
FUEL	Fuel Tank Capacity (Liter)	60	60
S	Front Weight Carrier, 55Kg		
FACTORY FITTED OPTIONS	Up to 2 Remote Valve		
ROPS with Fiber Canopy			

USAGE IN VARIOUS APPLICATIONS



CULTIVATOR

MB PLOUGH





SUGARCANE HAULAGE

STRAW REAPER



ROTAVATOR

LASER LEVELLER

CNH Industrial (India) Private Limited

Plot No. 03, Udyog Kendra, Greater Noida - 201306, District Gautam Budh Nagar, Uttar Pradesh





Note: New Holland believes in constantly working to bring improvements in their products. Therefore, the specifications given above may be changed without any prior notice. For latest information, contact your nearest dealership. The specifications given above are taken from the sub-clause of CFMTTI, Budni, Report/manufacturer's website/product leaflet.

20-110 HP