The new STEYR PLUS series from 80 hp to 120 hp

### EVERYONE DESERVES A PLUS





### THE ULTIMATE ALL-ROUND **VERSATILITY**

An iconic product name of the STEYR brand, the PLUS series returns to create a powerful link between our rich history and strong future.

### The result: STEYR PLUS, more than you expect, just what you deserve

The ultimate all-round versatility for today's modern mixed and livestock farms. Whether it is doing loader work, working with front or rear mounted implements, transport, or even in confined spaces, the PLUS delivers maximum performance and comfort.

The bold and dynamic look express the force of our modern design, that makes it look like larger high-power tractors.

A 3.6 l FPT Industrial engine, with power from 80 to 117 hp, gives a wide choice of models to fit all end users' needs.

>> It does it all, better.





# EASE OF USE IS A GREAT PLUS



Axle-guided front hitch.



Impressive manoeuvrability with the Powershuttle.



Class 1.0 HD and 1.5 HD front axles ideal for intensive loader work.



Combinations of tyres and wheels to suit every type of application.



40 kph ECO- speed on S-Control 2 transmission for reduced fuel consumption.



Increased Gross Vehicle Weight of 7,000 kg.



S-Control 2 - 24x24 2-speed Powershift transmission with Powershuttle.



Ergonomic operation using the Multicontroller.



High lift capacity of up to 5,000 kg with increased capacity 80 l/min pump.



S-Guide Autoguidance ensuring up to 1.5 cm pass-to-pass and year-over-year accuracy.



Superlative visibility with Hi-Visibility roof panel and redesigned exhaust.



Loader Ready with complete loader package from factory.



New suspended cab.



Mechanical Front Hitch with front PTO.



Brake to Clutch for smooth control of the tractor and Stop & Go functionality.



Mechanical Draft Control or Electronic Draft Control.



Variable Ratio Steering reducing the lock-to-lock turns of the steering wheel.



Lift-O-Matic system offers fast implement raising and lowering.


# GET A PLUS IN ALL SUBJECTS






### Plus in versatility

Class 1.0 HD and 1.5 HD front axles to suit all needs, complete loader package from factory for loader plug-and-play, up to 16.9 R38 tyres and increased Gross Vehicle Weight of 7,000 kg emphasise the multiform talent of this series.




### Plus in productivity

Powerful and efficient 3.6 l FPT Industrial engine with power from 80 to 117 hp, 80 l/min pump for increased responsiveness, up to 5,000 kg lift capacity, and new light package provide the right equipment to produce more with less.



#### Plus in comfort

New cab suspension for a smooth ride, new clear display of the machine's parameters and settings, Hi-Visibility roof panel, Brake to Clutch and Variable Ratio Steering help to make long working days much more comfortable.



#### Plus in precision

S-Guide Autoguidance ensures up to 1.5 cm pass-topass and year-over-year accuracy, allowing accurate application of production inputs. With 5 years S-Fleet Telematics, agronomic decisions can be taken on-the-go thus improving productivity and efficiency.

MODEL		PLUS		PLUS		PLUS		PLUS		PLUS		
TRANSMISSION												
	S-Control 2 – 24x24 2-speed Powershift with Powershuttle, 40 kph											
ENGINE												
FPT F5 3.6 L Common Rail Diesel engine, turbocharged and intercooled / HI-eSCR2 technology / Stage V		4 / 3,600		4 / 3,600		4 / 3,600		4 / 3,600		4 / 3,600		
Number of cylinders / Capa	icity [cm³]											
<b>Max. engine power</b> ECE R120¹¹ [kW/hp]	Rated engine power ECE R120 <sup>1)</sup> [kW/hp]	59 / 80	59 / 80	66 / 90	66 / 90	74 / 100	74 / 100	81 / 110	81 / 110	86 / 117	86 / 117	
<b>Engine speed</b> at max. engine power [rpm]	Rated engine speed [rpm]	1,900	2,300	1,900	2,300	1,900	2,300	1,900	2,300	1,900	2,300	
Max torque [Nm @ 1,300 rpm]		330		380		450		490		506		
Torque increase OECD [%]		34.7		38.7		46.5		45.7		41.7		
HYDRAULIC												
	Open Center pump - 82 l/min Up to 3 mechanical rear remotes 2 mechanical mid mounts, joystick Lift-O-Matic system offers fast raising and lowering											
PTO												
			540 / 540E / 1,000 @ 1,938 / 1,535 / 1,926 rpm									
REAR LINKAGE												
	MDC Mechanical Draft Control or EDC Electronic Draft Control - max. lift capacity 5,000 kg											
CONFIGURATION												
		Mechanical front hitch with front PTO STEYR S-front loader, new U range with quick coupler, vibration damping & collision protection										
		S-Stop (Brake to clutch)										

**STEYR 4090** 

**STEYR 4080** 

You drive better when you are safe. Before using this vehicle, please read the Operating Manual and become familiar with the use of each of the controls. Note the contents of the instruction panels and use the safety equipment for your own personal safety. This brochure is intended for use internationally. The availability of a few models and of standard and special equipment items may vary from one country to another.



STEYR reserves the right at any time and without prior announcement to make changes to the design and technical version without this in any way obliging STEYR to transfer these to units already sold.

Details, descriptions and pictorial material reflect the current status at the date of publication, but can be amended without prior announcement and at any time. Pictorial materials may show certain national versions, items of special equipment as well as non-complete standard versions.

TP01 / SM / 03.24 / Printed in Austria - Cod. n. 23S0018COMINB www.steyr-traktoren.com











**STEYR 4110** 

**STEYR 4120** 

**STEYR 4100** 

 $<sup>^{\</sup>rm 1)}$  ECE R120 complies with ISO 14396 and 97/68EC