

New Holland BC5060 Series Square Baler



Your growth, our technology.



New Holland 5060 Baler Specification

Hydroformatic bale tensioning with HD Knotter

Bale Size:

Cross Section	14 x 18 in. (36x 46 cm)
Length	Audjustable,12 to 52 in. (31 to 132 cm)

Super-Sweep Pickup:

Width on flare	1.8 m
Number of teeth	110 on 5 tooth bars
Floating windguard	8 rods
Drive	V-belt roller chain to lost motion reel drive
Gauge wheel	3.00 x 12; semi-pneumatic

Rotary Feeding System:

Type	Packer fork in combination with 2 paired rotors
Drive	Chain from main drive shaft; sealed ball bearings on all shafts

Feed opening

1826 cm

Plunger:

Stroke length	76.2 cm
Speed (540 rpm)	93 SPM
Construction	High-strength steel throughout; modified extension is built into the plunger face, eliminating the need for bolt-on extensions

Tying Mechanisms:

Type	HD Knotter
Protection	Shearbolt
Capacity (twine)	6 balls
Capacity (wire)	4 coils

Main Drive:

Flywheel diameter	56 cm
PTO	3 joint
Protection	Hearbolt, overrunning & slip clutches
Gearbox	poird with tapered roller bearings; heat-treated alloy steel running in oil

Tires:

Floating (right)	27 x 9.50-15, 6 PR
Floating (left)	31 x 13.50-15, 6 PR

Dimensions:

Height (max.)	178 cm
Width	279 cm

Length:

With 3-joint PTO & quarter-turn bale chute	626 cm
--------------------------------------------	--------

Weight (approximate):

With 3-joint PTO, twine version	1542 kg
---------------------------------	---------

Recommended Transport Speed:

32 km / h

Tractor requirement:

55 - 75 HP

Inno/Leaf/5060 Baler/Eng.

New Holland Fiat (India) Pvt. Ltd.

Plant: Plot No. 03, Udyog Kendra, Greater Noida-201306, Distt. Gautam Budh Nagar
Uttar Pradesh, Ph: 0120-3056000, Fax: 0120-3056989
Toll Free Number- 1800 419 0124



Your growth, our technology.