



THE NEW ERA IN CONSTRUCTION EQUIPMENT
Presenting
THE ALL-NEW

450 NX CEVS

TANDEM VIBRATORY COMPACTOR



SCAN ME



Eco-Friendly, High-Efficiency
Powerful Engine

myCASE
CONSTRUCTION

The New Gen of Telematics



Reliable
Hydraulics



REASONS TO CHOOSE NX SERIES

A LEGACY OF HIGH PERFORMANCE



EFFICIENCY AND RELIABILITY

- Optimized machine weight and repowering with 18.5 KW CEV Stage V engine, with mechanical fuel pump ensures peace of mind
- Intelligent hydraulic system and 25HP engine delivers high efficiency than CEV-V 45hp models.
- Well protected rust proof plastic fuel tank with lockable cap




EXCELLENT SERVICEABILITY

- Single piece openable engine hood with provision to lock
- Engine and all serviceable parts are easily accessible
- Ease of accessibility of Hydraulic pumps, Valve block, from Hood opening.
- Gas strut assisted engine hood for ease of lifting and serviceability



SAFETY ENHANCED

- Two post foldable ROPS structure for better visibility and ease of ingress/egress
- Electro Magnetic Immunity and compliance
- Both sides rear-view mirror
- Excellent visibility of drum edges thanks to optimized width
- New ergonomic footsteps



A LEGACY OF HIGH PERFORMANCE & INNOVATION

- Powered by M&M 275DI mechanical engine
- 180+ years of legacy, delivering breakthrough technology
- Compact design for hassle-free maintenance
- High static linear load ensures good mat finish



COMFORTABLE OPERATOR STATION

- New operator station with newly designed controls and speed settings
- Best in class ergonomically designed comfortable seat with adjustable arm rest and high back-rest
- Wide canopy for better sun and rain protection
- High backrest seat with mechanical suspension with adjustments such as weight setting, backrest incline, arm rest position, forward and backward movement.



NEW CONNECTED MACHINES



- Enhanced monitoring and streamlined operations with my CASE Construction Telematics
- Boosted productivity through efficient resource allocation with fleet management
- Improved safety and security with advanced tracking and recovery capabilities
- Real-time data and downtime reduction for superior customer service
- Data-driven decision-making to increase profitability

SMART DESIGN

- Compact contemporary looks
- New robust frame suitable for confined space
- New intuitive instrument cluster with Vandal Guard
- Plastic water tank with strainer/filler for clean water, rust free for lifetime, 150L big size.
- Plastic fuel tanks with strainer and lockable cap, rust free for lifetime, Vandalism protection from all sides. Ground level filling ease.
- The vehicle experiences reduced noise pollution due to the engine fan being positioned at the front
- Fuel level gauge on cluster and low water level sensor
- Standard drum width of 1m for ease of maneuverability



ENGINE	
Engine Make	Mahindra & Mahindra
Engine Model	275DI
Max. Gross Power (kW/hp) @2200 rpm (ISO 14396)	18.5/ 25
Displacement (L)	2.048
Max. Torque (Nm) @1200 rpm (ISO 14396)	130
Emission level	CEV Emission Stage-V
Type of Cooling	Liquid Cooled
POWERTRAIN	
Max speed (km/hr)	9.5
Max Gradeability (%)	35
STEERING	
Steering	Hydrostatic (Center Point Articulation)
Steering Angle	±27°
Turning Radius (m)	3.32
Oscillation angle (degree)	±10°
BRAKES	
Service Brakes	Hydrostatic
Parking Brakes	Spring applied, hydraulically released
SERVICE CAPACITIES	
Water Tank Capacity (L)	150
Fuel Tank Capacity (L)	38
Hydraulic Tank Capacity (L)	40
Engine Crank Case (L)	5
Coolant (L)	6.8
Water spray nozzles	5 nozzles per drum
Water tank material	Plastic

STANDARD EQUIPMENT	
12v Power Socket, 2 Frequency, both Drum or Single Drum Vibration, Sunroof, Horn, Front & Rear Working Lights, Hazard Lights & Parking Lights, Pressurized Water Sprinkler System, 2 Scraper Per Drum, Travel & Vibration Circuit Filter - Tank Mounted Type	
SAFETY FEATURES	
New Secondary Braking System, Automatic Parking Braking Incase Of Engine Shutdown, No Vibration In Neutral, New Radiator Fan Guard	
INSTRUMENTATION	
Fuel Level Indicators, Hydraulic Oil Level Indicator, Front & Rear Light Switch, New Digital Hour Meter, Drum & Frequency Selection Switch, Engine Coolant Temperature Gauge, Ignition Switch, Neutral Indicator, Battery Charging Indicator, Engine Oil Pressure Indicator, Parking Brake Indicator, Turn & Hazard Indicator, Filter Clogging Indicator	

ROPS- Rollover Protection Structure

*Consider operator weight ballasting and total weight of machine.

CIN: U29240DL1998PTC344616
CASE NEW HOLLAND CONSTRUCTION EQUIPMENT (INDIA) PRIVATE LIMITED
 Level-4, Rectangle-1, D-4, District Center, Commercial Complex, Saket, New Delhi – 110017
 Contact No.: 011-66544151
 Email: caseindia@cnhind.com

CaseCE.com 1800 4199 770

Follow us on    @caseceindia

NOTE: Standard and optional fittings can vary according to the demands and specific regulations of each country. The illustrations may include optional rather than standard fittings - consult your CASE dealer. Furthermore, CNH reserves the right to modify machine specifications without incurring any obligation relating to such changes.

DISCLAIMER: 2.5% variation on parameters may occur and is acceptable by the industry norms.

VIBRATION STAGES	
Vibration stages	Two
Frequency High (Hz)	61
Frequency Low (Hz)	46
Amplitude (mm)	0.5
Centrifugal Force (High) - per drum (kgf/kN)	2900 / 28.43
Centrifugal Force (Low) - per drum (kgf/kN)	1652 / 16.20
Maximum Applied Force - per drum (kgf/kN)	4380 / 42.95
OPERATING DATA	
Operating weight (kg)	2900
Front Axle load (kg)	1480
Rear Axle load (kg)	1420
Static Linear Load - Front / Rear (kg/cm)	14.8 / 14.2
DIMENSIONS	
A - Wheelbase (m)	1.925
B - Overall Width (m)	1.184
C - Rear overhang - Drum Centre to frame edge (m)	0.535
D1=D2 - Drum Diameter - Front/Rear (m)	0.700
H1-Total Machine Height (m)	2.697
H2 - Height to top of seat / Steering wheel (m)	1.827
K - Ground Clearance (m)	0.307
L - Total Length (m)	2.871
O1 - Side Overhang - Drum edge to frame (m)	0.092 (92mm)
S - Drum Thickness (m)	0.012 (12mm)
W1=W2 - Drum Width-Front / Rear (m)	1.000
F - Curb Clearance (mm)	560

