

# TRACTOR T7.315 HD

CNH  
INDUSTRIAL | CAPITAL



## FRONT HYDRAULIC LIFT

Two operations in a single passing, more versatility and productivity in the farm



## FPT ENGINE WITH EPM (EXTRA POWER ELECTRONIC MANAGEMENT)

High performance and low consumption



## PRECISION AGRICULTURE

Much more productivity in operations.



## CABIN WITH MORE COMFORT IN THE CATEGORY

Comfort Ride™ suspension, led-bulb lighting, more comfort and visibility during night operations



## HIGH HYDRAULIC FLOW (220 l/min)

Remote valves with flow adjustment and increased hydraulic lift capacity.



## AUTOCOMMAND CVT TRANSMISSION

It select the ideal gear automatically, according to the workload. More uniformity during the operations, ideal for any operation.



A Brand of CNH Industrial



SEMPRE COM VOCÊ



[www.newholland.com](http://www.newholland.com)

T7		T7.315 HD
<b>Engine FPT Stage V</b>		
Maximum power @ EPM	cv/hp	318 / 313
Nominal power - @ 2,100 rpm ISO14396	cv/hp	304 / 300
Maximum torque @ 1,400 rpm	Nm	1.282
Torque reserve	%	28
Cylinder / Displacement	no. / L	6 / 6,7
Aspiration / Valves	No.	eVGT / 4
Diesel fuel maximum capacity	L	630
AdBlue maximum capacity	L	96
Diesel fuel		B7
<b>Transmission</b>		
Auto Command™ Continuously Variable		Standard
StopStard		Standard
Advance management system (GSM)		Standard
Minimum / maximum speed	km/h	0,03 / 40
<b>Axles</b>		
Terralock™ system		Standard
Terraglide™ front axle suspension		Standard
Traction bar		Standard
Articulation angle - tires / track	° C	55
Turning circle	mm	5,7
<b>Hydraulic system</b>		
MegaFlow™ hydraulic flow	L/min	220
Lift capacity on the eyebolt	Kg	11058
Lift capacity at 610 mm from the eyebolt	Kg	9.280
Type of control-remote valve	EHR	Standard
Remote valves	N	5
Category of the rear hydraulics		CAT4
<b>Electrical system</b>		
Alternator	V / A.h	12 / 150
Battery	V / A.h	12 / 136
<b>Power take-off</b>		
Rear PTO		Electro-hydraulic
Axle		1 3/8 in. 6 and 21 splines
PTO speed w/ engine @1800 rpm	rpm	540/540E/1000/1000E
<b>Cabin</b>		
Noise level EC77/311	dBa	69
Cabin w/ Comfort Ride™ suspension		Standard
Rear view mirrors / electronic adjustment		Standard
360-degree view / Bluetooth radio		Standard
Air seat		Standard
20 led-lights		Standard
Automatic Air-conditioning		Standard
<b>Weight</b>		
Boarding weight	kg	10.500
Allowable operating weight	kg	16800
<b>Dimensions</b>		
Total length	mm	5.700
Total width	mm	2.656
Total height	mm	3.272
<b>Tire availability</b>		
Front / Rear (Michelin)		600/70 R30 / 800/70R
<b>Accuracy Farming</b>		
Monitor - IntelliView IV		Standard
Oministar/Centerpoint RTX signal		Standard
Universal Radar		Standard
ISOBUS		Standard

