

8 - SPECIFICATIONS

Fluids and lubricants

Fuel tank

Capacity	116.6 L (30.8 US gal)
Specifications	#2 Diesel ultra-low sulfur

Cooling system

Capacity	12.0 L (3.2 US gal)
Specifications	EXTENDED LIFE OAT COOLANT/ANTIFREEZE

Hydraulic system

Reservoir capacity	40.5 L (10.7 US gal)
System capacity:	50.2 L (13.3 US gal)
Specifications	PREMIUM HYDRAULIC OIL HV68 MULTI-GRADE AW

Grease fittings

Quantity	As required
Specifications	MULTI-PURPOSE MOLY GREASE EP / AW / NLGI 2 (Molydisulfide)

Engine crank case oil

Capacity - with filter change	8.5 L (9.0 US qt)
Specifications	No.1 ENGINE OIL™ SAE 10W-40 CK-4 SEMI-SYNTHETIC

Final track drive

Capacity - each side	1.6 L (1.7 US qt) +/- 0.1 L (0.1 US qt)
Specifications	HYPOID GEAR OIL EP SAE 80W-90

Emissions fluid

Reservoir capacity	12.4 L (3.3 US gal)
DEF/AdBLUE® low volume indicator	3.7 L (1.0 US gal)
Specifications	DEF/AdBLUE®