

MAXXUM 110 - 140 HP

MAXXUM

TRACTORS 110 - 140 HP



CASE **ih**

CASE **ih**

MODEL	MAXXUM 110 VALUE AND X LINE	MAXXUM 125 VALUE AND X LINE	MAXXUM 140 X LINE
ENGINE			
Engine Type / Emission Level	Case IH FPT Stage 3A		
Number of Cylinders / Fuel Type	4 Cyl / Mechanical Injection System	6 Cyl / Mechanical Injection System	
Engine Aspiration	Turbocharged and Intercooled		
Valves / Displacement (litres)	4.5	6.75	6.75
Bore x Stroke (mm)	104 x 132		
Rated Power ECE R1201) (kW/hp(CV))	82 / 112	93 / 127	104 / 141
Rated Engine Speed (rpm)	2200		
Maximum Torque (Nm/rpm)	510 / 1250	555 / 1250	625 / 1250
Torque Rise Standard	43%	38%	39%
Fuel Tank (litres)	176	250	
ELECTRICAL			
Alternator (Amp) / Battery (CCA)	120 Amp / 960 CCA		
Starting Power	12 Volt with solenoid switch		
TRANSMISSION			
Transmission (Std)	24F / 24R with Hi/Lo Powershift		
Transmission (Opt)	16F / 16R Semi Powershift and 12F / 12R Synchro Mesh		
Creeper Transmission Options	48 x 48 / 32x 32 / 24 x 24		
Rear Axle Std / Opt	Flange Axle	Flange / 98 inches	
Automatic Differential Lock	Electro - Hydraulic		
Service Brake	Hydraulically operated multiple wet disc brake, self adjusting		
Type	Electro - Hydraulic		
Front Axle Type Std / Opt	Cat 3	Cat 3 / Cat 4	Cat 3 / Cat 4
POWER TAKE OFF			
Engagement Type	Electro - Hydraulic		
Speeds Standard / Option @1830rpm	540 /1000		
Shaft type	1 3/8” 21 Splines 1 3/8” 6 Splines		
HYDRAULIC SYSTEM			
System Type	Fixed Displacement / CCLS		
Pump flow and system type main hydraulic Stand/Optional (l/min)	63 / 80 / 113		
System Pressure (bar)	210		
Standard Steering And Service Pump (lpm)	40		
Total Tractor Flow (lpm)	103 / 120 / 153		
3-Point Hitch Category Standard / Optional	Cat II Fixed / Cat II / III Quick Attach		
Three Point Linkage Maxium Lift Capacity (kg) @ Hook End From Std to Opt	3419 / 4781	3419 / 4781	3761 / 5284
Drawbar Vertical Capacity (kg)	-	-	-
Max. Number Of Remote Valves Standard / Optional	2 / 3 / 4		
Max. Number Of Mid Mount Valves With Electronic Joystick	2	2	2

MODEL	MAXXUM 110 VALUE AND X LINE	MAXXUM 125 VALUE AND X LINE	MAXXUM 140 X LINE
FRONT HITCH AND PTO			
Front PTO 1,000 Speed @ 1,800 Engine RPM		Optional	
Front Hitch Lift Capacity [kg]		Optional	
Front Max. Lift Capacity (kg) @ Hook End		3550	
SHIPPING WEIGHT & DIMENSIONS			
Estimated Weight – ROPS MFD (kg)	4340	4460	-
Estimated Weight – Cab MFD (kg)	4740	4860	4950
A: Approximate Total Length Front Weights [mm]	4292	4532	
B: Approximate Total Height (mm)	2856	2900	
C: Approximate Total Width (Across Rear Fenders. Excluding Duals Wheels)	2170		
D: Approximate Wheel Base	2412	2661	
E: Track Setting Front (mm)	1407 - 2108	1417 - 2134	
E: Track Setting Rear (mm)	1426 - 2026	1426 - 2026	
STANDARD TYPE			
Front	380/85R24	380/85R28	
Rear	420/85R38	460/85R38	



CNHI Industrial SA, Via Francesco Borromini 4, 6850 Mendrisio, Switzerland



Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **AKCELA** lubricants. 25MEACOMMAX001



caseih.com

CASE IH