

T9 PLM INTELLIGENCE

CNH CAPITAL



OPTIMAL BALANCE

Greater traction capacity, high drawbar pull and the ability to operate larger implements: all the field advantages provided by an articulated chassis.



SUPERIOR COMFORT

Cab with a new interior architecture, IntelliView™ 12 display, intuitive and fully customizable LCD screen, and configurable 360° LED lighting. Enhanced comfort and safety during operation.



LOW FUEL CONSUMPTION, HIGH PERFORMANCE

FPT engine with rated power from 425 to 645 hp, providing ample power reserve for the most demanding operations.



HYDRAULIC SUPERIORITY

Hydraulic system delivering 428 L/min, capable of operating several functions simultaneously without compromising hydraulic performance.



FIELD CONNECTIVITY AND PRECISION

New multi-constellation receiver compatible with two satellite correction signals. Comprehensive operation management through factory-integrated advanced telematics.



16 x 2 FULL POWERSHIFT TRANSMISSION

Automatic gearshift management and optimized speed progression for each operation. Maximum control and efficiency.



NEW HOLLAND

WITH YOU, SEASON AFTER SEASON

TECHNICAL SPECIFICATIONS T9 PLM INTELLIGENCE

SPECIFICATION		T9.470	T9.520	T9.580	T9.615	T9.700
ENGINE						
Maximum power with EPM	CV / hp	467 / 460	522 / 514	578 / 570	614 / 605	699 / 689
Rated power at 2,000 rpm, ISO 14396	CV / hp	425 / 419	475 / 468	525 / 517	555 / 547	645 / 636
Maximum torque at 1,400 rpm	Nm	1.989	2.222	2.459	2.681	3.061
PTO power at 1,811 rpm	CV	409	462	516	537	537
Torque rise	%	40				
Number of cylinders / displacement	N / cm³	6 / 12,9				
Maximum diesel fuel capacity	L	1.162		1.722		
Maximum DEF / AdBlue tank capacity	L	174		250		
Emissions level		Stage V				
TRANSMISSION						
Ultra Command™ Full Powershift		16 A x 2 R				
Minimum speed	km/h	4				
Maximum speed	km/h	40				
IntelliShift mode		Standard				
Ground Speed Management (GSM)		Standard				
AXLES						
TerraLock™ system		Automatic traction / differential lock management				
Drawbar		Cat. 4 HD			Cat. 5	
Articulation angle - tires / tracks	°	42			38	
Turning radius	mm	4.900			5.700	
HYDRAULIC SYSTEM						
Hydraulic flow	L/min	428				
Lift capacity at 610 mm behind the hitch point	kg	9.072			8.900	
Remote control valve type		Electro-hydraulic				
Rear remote valves with pressure release	N	6				
Hydraulic three-point hitch		Optional			-	
ELECTRICAL SYSTEM						
Alternator	V / A	14 / 200				
Two batteries	V / Ah	12 / 100				
PTO						
Rear PTO engagement		Electro-hydraulic				
Output shaft		1 3/4 in, 20 splines				
PTO speed at 1,800 engine rpm	rpm	1.000				
CAB						
Noise level EC77/311	dBA	74				
Comfort Ride™ cab suspension system		Standard				
Air-suspension seat		Standard				
Automatic air conditioning		Standard				
WEIGHT						
Shipping weight	kg	22.644	25.264	25.627	27.288	30.202
Maximum permissible operating weight with hitch	kg	24.166		24.620	-	-
Maximum permissible operating weight	kg	25.401			27.216	30.391
DIMENSIONS						
Overall length	mm	7.493			7.615	
Overall width	mm	4.419				
Overall height	mm	3.380				
TIRES						
Front / rear tires		VF 800/70R38 dual				
Front / rear rice tires, optional		520/85R42 dual				
PRECISION FARMING						
IntelliView™ 12 display		Standard				
Cygnus™ antenna		Standard				
Lifetime FieldOps™ telematics		Standard				
IntelliTurn™ - automated end-of-row turning		Optional				
Six-product control		Standard				
Core technology package: ISOBUS Class 2; PLM 3 PRO for 3 years, pass-to-pass accuracy and repeatability of +/- 2.5 cm.		Standard				

With New Holland you get the best options in agricultural machinery. And in financing too. Ask about our factory-direct financing plans.

The dimensions, weights and capacities shown in this brochure, as well as any conversion used, are always approximate and subject to normal variations within manufacturing tolerances. It is New Holland's policy to continuously improve its products, and New Holland reserves the right to modify specifications and materials, and to introduce improvements at any time, without prior notice or obligation of any kind. The illustrations in the brochure do not necessarily show the product in standard condition. Some optional items are produced to order only. **September 2026.**

AT YOUR DEALERSHIP: