The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
SECTION 1. PRODUCT AND COM	MPANY IDENTIFICATION	
Product name	: Case No. 1 Engine Oil Semi-Synth	netic SAE 10W-40 CK-4
Product code	: 00114286	
Manufacturer or supplier's d Supplier Telephone Telefax	details : TransDiesel Limited NZBN 9429036551132 533 Halswell Junction Road Christchurch 8042 New Zealand : 0800 848 267 (All Hours) :	
Emergency telephone number	: 0800 848 267 (All Hours)	
Recommended use of the cl Recommended use	hemical and restrictions on use : Engine oil.	

SECTION 2. HAZARDS IDENTIFICATION

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2017., Not classified as Dangerous Goods for transport, according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Hazard classification

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.

Precautionary statements

Prevention:

No precautionary phrases.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
	Response: No precautionary phrases.	
	Storage:	

No precautionary phrases.

Disposal: No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature		Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-

9, 68649-12-7, 151006-60-9, 163149-28-8.

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90
Alkylated phenol ester	125643-61-0	Aquatic Chronic4; H413	1 - 3
Alkaryl amine	36878-20-3	Aquatic Chronic4; H413	1 - 3
Zinc dialkyldithiophosphate	113706-15-3	Acute Tox.5; H303 Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Acute2; H401 Aquatic Chronic2; H411	1 - 2.49
Alkylphenol	27193-86-8	Skin Corr.1C; H314 Eye Dam.1; H318 Repr.1B; H360F Aquatic Acute1; H400 Aquatic Chronic1; H410	0.1 - 0.24

For explanation of abbreviations see section 16.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020 Print Date 22.10.2020		
SECTION 4. FIRST-AID MEASUR)		
If inhaled	No treatment necessary under normal conditio If symptoms persist, obtain medical advice.	ns of use.	
In case of skin contact	Remove contaminated clothing. Flush exposed water and follow by washing with soap if availa If persistent irritation occurs, obtain medical at	able.	
In case of eye contact	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to rinsing. If persistent irritation occurs, obtain medical at		
If swallowed	In general no treatment is necessary unless la are swallowed, however, get medical advice.	rge quantities	
Most important symptoms and effects, both acute and delayed	Oil acne/folliculitis signs and symptoms may in of black pustules and spots on the skin of expo Ingestion may result in nausea, vomiting and/c	osed areas.	
Protection of first-aiders	When administering first aid, ensure that you a appropriate personal protective equipment acc incident, injury and surroundings.		
Notes to physician	Treat symptomatically.		

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media		oam, water spray or fog. Dry chemical powder, carbon lioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: D	Do not use water in a jet.
Specific hazards during firefighting	A gi C o	lazardous combustion products may include: complex mixture of airborne solid and liquid particulates and ases (smoke). Carbon monoxide may be evolved if incomplete combustion ccurs. Inidentified organic and inorganic compounds.
Specific extinguishing methods		Ise extinguishing measures that are appropriate to local ircumstances and the surrounding environment.
Special protective equipment for firefighters	gl	Proper protective equipment including chemical resistant loves are to be worn; chemical resistant suit is indicated if arge contact with spilled product is expected. Self-Contained

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020	
	0 11	Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to	
	relevant Standards (e.g. Europe: E	N469).	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	void contact with skin and eyes.	
Environmental precautions	se appropriate containment to avoid environ ontamination. Prevent from spreading or ent tches or rivers by using sand, earth, or othe arriers.	ering drains,
	ocal authorities should be advised if significa annot be contained.	int spillages
Methods and materials for containment and cleaning up	lippery when spilt. Avoid accidents, clean un revent from spreading by making a barrier wo other containment material. eclaim liquid directly or in an absorbent. bak up residue with an absorbent such as cluitable material and dispose of properly.	ith sand, earth
Additional advice	or guidance on selection of personal protect se Section 8 of this Safety Data Sheet. or guidance on disposal of spilled material s is Safety Data Sheet.	

SECTION 7. HANDLING AND STORAGE

General Precautions	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact	: Strong oxidising agents.
Product Transfer	: Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
Storage		
Other data	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.	
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers or constant steel or high density polyethylene. Unsuitable material: PVC.	ontainer linings, use mild
Container Advice	: Polyethylene containers should not be temperatures because of possible risk	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	WES-TWA (Mist)	5 mg/m3	NZ OEL
	Further information: Sampled by a method that does not collect vapour.			
Oil mist, mineral	Not Assigned	WES-STEL (Mist)	10 mg/m3	NZ OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil Engineering measures : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good busekeening	ersion 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil Engineering measures The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.			IFA) , Germany
 vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. 			www.inrs.fr/accueil
General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.	Engineering measures	vary depending upon potential expo controls based on a risk assessmen Appropriate measures include: Adequate ventilation to control airbo Where material is heated, sprayed o	osure conditions. Select at of local circumstances. orne concentrations. or mist formed, there is
 Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. 			ntrations to be generated.
measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.		Define procedures for safe handling controls.	
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.		measures relevant to normal activiti	
Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.		Ensure appropriate selection, testing equipment used to control exposure	e, e.g. personal protective
subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.		Drain down system prior to equipme maintenance.	ent break-in or
washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.		subsequent recycle.	
		washing hands after handling the m drinking, and/or smoking. Routinely protective equipment to remove con	aterial and before eating, wash work clothing and ataminants. Discard
	Personal protective equipmen	•	

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

If engineering controls do n	idustrial hygiene practices,
concentrations to a level wh	en to avoid breathing of material.
health, select respiratory pr	not maintain airborne
specific conditions of use a	hich is adequate to protect worker
Check with respiratory prote	rotection equipment suitable for the
Where air-filtering respirato	and meeting relevant legislation.
appropriate combination of	tective equipment suppliers.
Select a filter suitable for th	ors are suitable, select an

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020 Print Date 2	2.10.2020
	(149°F)].	
Hand protection Remarks	Where hand contact with the product may occur the u gloves approved to relevant standards (e.g. Europe: US: F739) made from the following materials may pro- suitable chemical protection. PVC, neoprene or nitrile gloves Suitability and durability of a glove is depende usage, e.g. frequency and duration of contact, chemi- resistance of glove material, dexterity. Always seek a from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effect care. Gloves must only be worn on clean hands. Afte gloves, hands should be washed and dried thoroughl Application of a non-perfumed moisturizer is recomm	EN374, pvide e rubber ent on cal dvice e tive hand r using y.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with pre- for > 480 minutes where suitable gloves can be ident short-term/splash protection we recommend the sam recognize that suitable gloves offering this level of pre- may not be available and in this case a lower breakth time maybe acceptable so long as appropriate mainter and replacement regimes are followed. Glove thickness a good predictor of glove resistance to a chemical as dependent on the exact composition of the glove mat Glove thickness should be typically greater than 0.35 depending on the glove make and model.	ified. For e but otection nrough enance ess is not it is terial.
Eye protection	If material is handled such that it could be splashed in protective eyewear is recommended.	nto eyes,
Skin and body protection	Skin protection is not ordinarily required beyond stan work clothes. It is good practice to wear chemical resistant gloves.	dard
Thermal hazards	Not applicable	
Environmental exposure cor	ls	
General advice	Take appropriate measures to fulfill the requirements relevant environmental protection legislation. Avoid contamination of the environment by following advice Section 6. If necessary, prevent undissolved materia being discharged to waste water. Waste water should treated in a municipal or industrial waste water treatm	e given in Il from d be

before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

rsion 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
CTION 9. PHYSICAL AND CHE	MICAL PROPERTIES	
Appearance	: Liquid at room temperature.	
Colour	: amber	
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: -36 °C / -33 °FMethod: ASTM D97	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)	
Flash point	: 221 °C / 430 °F Method: ASTM D92 (COC)	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Data not available	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: > 1estimated value(s)	
Density	: 866 kg/m3 (15.0 °C / 59.0 °F) Method: ASTM D4052	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6(based on information of	n similar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 96.5 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	
	14.3 mm2/s (100 °C / 212 °F)	

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020 Method: ASTM D445	Print Date 22.10.2020
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be	e a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity:

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
	Based on available data, the classification criteria are not met.	

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Components:

Zinc dialkyldithiophosphate:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification	
Highly refined mineral oil	No carcinogenicity classification.	

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
Reproductive toxicity		

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
----------------------	--

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020 Print Date 22.	10.2020
Ecotoxicity		
Product:		
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are n	iot met.
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are n	iot met.
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are n	iot met.
Toxicity to fish (Chronic	: Remarks: Data not available	
toxicity) Toxicity to crustacean (Chronic toxicity)	: Remarks: Data not available	
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available	
<u>Components:</u> Alkylphenol :		
M-Factor (Short-term (acute) aquatic hazard)	: 10	
M-Factor (Long-term (chronic) aquatic hazard)	: 10	
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegradable., Major constituent inherently biodegradable, but contains components tha persist in the environment.	
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.	
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on information on similar products)	
Mobility in soil		
Product:		
Mobility	 Remarks: Liquid under most environmental conditions., enters soil, it will adsorb to soil particles and will not be mobile. 	

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
	Remarks: Floats on water.	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	 Does not have ozone depletion poterozone creation potential or global war is a mixture of non-volatile componereleased to air in any significant quar conditions of use. Poorly soluble mixture., Causes phy organisms. Mineral oil does not cause chronic to organisms at concentrations less that 	arming potential., Product ints, which will not be ntities under normal sical fouling of aquatic pxicity to aquatic

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal methods, including disposal of packaging, should be in accordance with the Hazardous Substances (Disposal) Notice 2017 and the Act.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks :	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0 Revision Date 25.08.2020 Print Date 22.10.2020
Land Transport Rule:

Land Transport Rule: Dangerous Goods 2012 -NZS 5433 Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

R-phrase(s)	:	Not classified.
S-phrase(s)	:	Not classified.

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Workplace Exposure Standards and Biological Exposure Indices November 2017. New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Other international regulations

The components of this product are reported in the following inventories:

EINECS	: Not all components listed.
TSCA	: All components listed.
NZIoC	: All components listed.

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H360F	May damage fertility.	
H400	Very toxic to aquatic life.	
H401	Toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic	life.
Full text of other abbre	eviations	
Acute Tox.	Acute toxicity	
Aquatic Acute	Short-term (acute) aquatic hazard	
Aquatic Chronic	Long-term (chronic) aquatic hazard	
Asp. Tox.	Aspiration hazard	
Eye Dam.	Serious eye damage	
Repr.	Reproductive toxicity	
Skin Corr.	Skin corrosion	
Skin Irrit.	Skin irritation	

Abbreviations and Acronyms

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response: ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative: WHMIS - Workplace Hazardous Materials Information System

Further information

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Case No. 1 Engine Oil Semi-Synthetic SAE 10W-40 CK-4

Version 1.0	Revision Date 25.08.2020	Print Date 22.10.2020
Training advice	Provide adequate informati operators.	on, instruction and training for
Other information	A vertical bar () in the left r from the previous version.	nargin indicates an amendment
Sources of key data used to compile the Safety Data Sheet	sources of information (e.g.	but not limited to, one or more . toxicological data from Shell uppliers' data, CONCAWE, EU 2 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN