

FARMALL

LIFESTYLE RANGE



CASE IH





25B

BIG PERFORMANCE IN A SMALL PACKAGE

With its proven three cylinder, high torque diesel engine and easy to operate two-range hydrostatic transmission, these purpose built compact tractors are perfect for pulling trailers and light implements, mowing and front loader work.

FARMALL 25B HYDRO

PLUS LOADER

Challenge PLc05 front end loader with 4-in-1 Bucket



SCAN FOR VIDEO WALKTHROUGH



Models	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall 25B	Mitsubishi	3 cylinder diesel	1.32 l	27 (20)	79 Nm	25 litres	650kg	730kg	Challenge PLc05	Standard or 4-in-1	1.79m	190kg

**To Pivot pin. *Rated Operating Load.





35B

FOR THE SERIOUS LIFESTYLE FARMER

With its fuel efficient 4-cylinder engine and 1,385kg dry weight, the Farmall 35B takes lifestyle farming to a whole new level. With a host of standard features normally found on larger tractors, it's no wonder the Farmall 35B is the most popular model in the Case IH lifestyle range.

FARMALL 35B SYNCHRO

PLUS LOADER

Challenge PLc10 front end loader with 4-in-1 Bucket

FARMALL 35B HYDRO

PLUS LOADER

Challenge PLc10 front end loader with 4-in-1 Bucket



SCAN FOR VIDEO WALKTHROUGH



MODEL	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall 35B	Mitsubishi	4 cylinder diesel	1.76 l	38 (28)	103 Nm	33 litres	820kg	Synchro 1385kg / Hydro 1403kg	Challenge PLc10	Standard or 4-in-1	2.45m	375kg

**To Pivot pin. *Rated Operating Load.





50B

THE PROFESSIONAL'S CHOICE

2.5L four cylinder diesel power matched with either a three range hydro or 16x16 synchro transmission means you're always prepared for the toughest challenge. Ag tyres are fitted as standard, or choose Industrial to suit your operation.

FARMALL 50B SYNCHRO

PLUS LOADER

Challenge PLc15 front end loader with 4-in-1 Bucket

FARMALL 50B HYDRO

PLUS LOADER

Challenge PLc15 front end loader with 4-in-1 Bucket



SCAN FOR VIDEO WALKTHROUGH



MODEL	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall 50B	LS Mitron	4 cylinder diesel	2.5 l	47 (35)	140 Nm	36 litres	1252kg	Synchro 1650kg / Hydro 1680kg	Challenge PLc15	Standard or 4-in-1	2.7m	420kg

**To Pivot pin. *Rated Operating Load.





60B

TO TACKLE THE BIG JOBS

The Farmall 60B is the popular choice of the Case IH lifestyle range. Its turbocharged engine delivers effortless power – and an array of impressive features such as two sets of hydraulic remotes and three-speed PTO are fitted as standard. Also available with an air-conditioned cab.

FARMALL 60B SYNCHRO ROPS

PLUS LOADER

Challenge PLc15 front end loader with 4-in-1 Bucket

SCAN FOR VIDEO WALKTHROUGH



FARMALL 60B SYNCHRO CAB

PLUS LOADER

Challenge PLc15 front end loader with 4-in-1 Bucket

SCAN FOR VIDEO WALKTHROUGH



MODEL	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall 60B	LS Mitron	4 cylinder diesel	2.5 l	57 (43)	170 Nm	80 litres	1850kg	Cab 2370kg ROPS 2165kg	Challenge PLc15	Standard or 4-in-1	2.84m	Cab 810kg ROPS 790kg

**To Pivot pin. *Rated Operating Load.





JXM 55

BIG TRACTOR, SMALL PRICE

The Farmall JXM 55 is the entry level model for the Farmall JXM range. Its large frame allows heavy duty tasks to be performed with minimum effort. The 3-cylinder 2.9 litre turbocharged engine provides outstanding horsepower in its class. The Farmall JXM series tractors reliably and cost effectively deliver power and performance, just what Case IH owners expect.

FARMALL JXM 55

PLUS LOADER

Challenge PL20 front end loader with 4-in-1 Bucket



SCAN FOR VIDEO WALKTHROUGH



MODEL	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall JXM 55	FPT S8000	3 cylinder diesel	2.91	55 (41)	213 Nm	60 litres	2500kg	2740kg	PL20	Standard or 4-in-1	3.10m	675kg

**To Pivot pin. *Rated Operating Load.





JXM 65

MORE POWER, MORE OPTIONS

The Farmall JXM 65 is latest model offering in the Farmall JXM range. A 3-cylinder 2.9 litre turbocharged and intercooled engine delivers real power so that you'll be able to perform all the tasks you need. With a competitive price to match its performance the Farmall JXM 65 is guaranteed to be a popular choice.

FARMALL JXM 65

PLUS LOADER

Challenge PL20 front end loader with 4-in-1 Bucket



SCAN FOR VIDEO WALKTHROUGH



MODEL	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall JXM 55	FPT S8000	3 cylinder diesel	2.91	65 (49)	265 Nm	60 litres	2500kg	2740kg	PL20	Standard or 4-in-1	3.10m	675kg

**To Pivot pin. *Rated Operating Load.



75JXM CASE IH

CASE IH

75JXM





JXM 75

ANY TASK, ANY TIME

The Farmall JXM 75 has a reputation as a workhorse, and with a choice of shuttle options it is well suited to loader work. With a rugged frame powered by a 3-cylinder 2.9 litre turbocharged and intercooled engine, performance is never compromised. Designed with operator comfort in mind the Farmall JXM 75 is a robust machine that will perform day in day out.

FARMALL JXM 75

PLUS LOADER

Challenge PL20 front end loader with 4-in-1 Bucket”



SCAN FOR VIDEO WALKTHROUGH



MODEL	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall JXM 75	FPT S8000	3 cylinder diesel	2.91	75 (56)	306 Nm	60 litres	2500kg	2810kg	PL20	Standard or 4-in-1	3.10m	704kg

**To Pivot pin. *Rated Operating Load.



CASE IH
FARMALL

90JXM

15 T
LOAD
LIMIT



JXM 90

PROFESSIONAL PACKAGE WITH VALUE

The Farmall JXM 90 is the top of the Farmall JXM range, and with good reason. The 4-cylinder 3.9 litre turbocharged and intercooled engine and dry weight of 3,250kg results in a premium machine that ensures productivity. Combined with an ergonomic operator area and long up times the Farmall JXM 90 is the tractor you need when the going gets tough.

FARMALL JXM 90

PLUS LOADER

Challenge OL30 front end loader with 4-in-1 Bucket”



SCAN FOR VIDEO WALKTHROUGH



MODEL	Engine	Type	Size	HP (kW)	Torque	Fuel Tank	Rear Lift Capacity	Dry Weight	Front End Loader	Bucket Type	Max Lift Height**	ROL*
Farmall JXM 90	FPT S8000	4 cylinder diesel	3.91	88 (66)	340 Nm	90 litres	2500kg	3250kg	OL30	Standard or 4-in-1	3.26m	810kg

**To Pivot pin. *Rated Operating Load.

SPECIFICATIONS	FARMALL 25B	FARMALL 35B	FARMALL 40B	FARMALL 50B	FARMALL 60B
ENGINE					
Model	Mitsubishi		LS Mtron		
No. of Cylinders / aspiration	3 / Natural		4 / Natural		4 / Turbo
Capacity (Litres)	1.318	1.758		2.505	
Bore/Stroke (mm)	78 x 92		88 x 103		
Engine rated power @ 2300 rpm (kW/hp)	20 / 27	28 / 38	30 / 41	35 / 47	43 / 57
PTO power at rated speed (kW/hp)	20 / 27	Hydro - 22 / 29 / Mech - 23 / 31	25 / 34	Hydro - 27 / 37 / Mech - 29 / 39	35 / 47
Maximum torque at 1400 rpm (Nm)	79	103	130	140	170
Fuel tank capacity (Litres)	25	33	36		80
Rated Speed (RPM)	2700		2600		
TRANSMISSION					
Type	Hydrostatic	Hydrostatic & Mechanical	Mechanical	Hydrostatic & Mechanical	Mechanical
Gears	2 range HST	3 range HST & 12 x 12 Mech	16 x 16 Mech	3 range HST & 16 x 16 Mech	16 x 16 Mech
Speed Range Hydrostatic (kmph)	0 - 15.7	0 - 25	N/A	0 - 25	N/A
Speed Range Mechanical (kmph)	N/A	1.2 - 24	1.2 - 27		1.2 - 32
PTO					
Type	Independent				
Reat PTO Standard (rpm)	540				540/750/1000
Engagement	Electro-Hydraulic				
HYDRAULICS					
Type	Gear Pump				
Capacity (L/min) - Excludes Steering and Transmission	10	30	29		36
Maximum number of remote valves	1			2 Front / 2 Rear	
Rear linkage Category	Cat I				Cat II
Link Ends	Ball				
Maximum Lift Capacity (kg)	650	820	1252		
FRONT AXLE					
Type	4WD Flange				
Steering	Hydrostatic				
Turning Radius without Brakes (m)	2.62	3.05	3.08		3.3
Inter Axle Ratio	1.520:1	1.700:1	1.486:1		1.423:1
REAR AXLE					
Type	Flange				
Difflock type	Mechanical				
ELECTRICAL SYSTEM					
System Voltage (v)	12				
Alternator rating (A)	50amp				
Battery (CCA)	80AH		100AH		
DRAWBAR					
Drawbar Type	Swinging Drawbar with Clevis				
DIMENSIONS					
*Approximate Shipping Weight - (kg)	730	*1403 - Hydro / 1385 - Mech.*	1620	*1680 - Hydro / 1650 - Mech.*	*2165 - ROPS / 2370 - Cab*
*Ground Clearance - Under Drawbar (mm)	290	300	372	372	407
Wheelbase (mm)	1500	1674	1758		2047
*Overall Length (mm)	2660	2987	3192		3556
*Overall Width (mm)	1226	1333	1672		1700
*Overall Height (mm)	2370	2352	2416	2447	*2650 - ROPS / 2465 - Cab*
* Indicative only - Will vary depending on specification & wheel equipment					
DIMENSIONS					
Loader Model (Challenge Prime Lift Compact)	PLc05	PLc10	PLc15	PLc15	PLc25
*Lift Height (pivot pin)	1850mm	2450mm	2703mm	2703mm	2900mm
Rated Operating Load - STD Bucket/Loader/Tractor	188kg	265kg	415kg	415kg	*725kg - ROPS / 790kg - Cab*
Loader Lift Capacity kg - Max (Loader Only)	439kg	739kg	1062kg	1062kg	2361kg
Bucket Width mm (inches)	1340 (52)	1500 (59)	Up to 1700 (67)	Up to 1700 (67)	Up to 1860 (73)
Counterweight Recommendation	250kg	390kg	555kg	555kg	*790kg - ROPS / 810kg - Cab*
* Indicative only - Will vary depending on specification & wheel equipment					

SPECIFICATIONS	FARMALL JXM 55	FARMALL JXM 65	FARMALL JXM 75	FARMALL JXM 90
ENGINE				
Model	FPT (IVECO S8000)			
Emission	Tier III			
No. of Cylinders / Aspiration	3 / Turbocharged	3 / Turbocharged Intercooled		4 / Turbocharged Aftercooled
Capacity (Litres)	2,9			3,9
Bore x Stroke	104 x 115			
Engine Rated Power	41 / 55	48.5 / 65	56 / 75	65.7 / 88
PTO Power	37.3 / 50	42.5 / 57	50 / 67	57.0 / 76
Maximum torque	213	265	306	340
Torque Rise %	25	32	32	25
Fuel Tank Capacity	60 • + 40			90
TRANSMISSION				
Power Shuttle	•			
Synchro-Mechanical	•			
12 x12 Mechanical	•			
20 x 20 Mechanical	◦			
Minimum/Maximum	1.54 / 32.10	1.59 / 33.30	1.65/34.50	
Creeper	0.27 / 32.10	0.28 / 33.3	0.29	
PTO				
Independent PTO	•			
Rear PTO	540/540E			
HYDRAULICS				
Draft Sensing	Top Link			
Rear Linkage Capacity	I-II			
Stabiliser and Link Ends	Chain - Fixed/Telescopic - Flexible			
Mechanical Lift Control	Position, draft, mixed / Fast Raise-Lower			
Main Pump Flow	60			
Steering Pump Flow	26/31			
Maximum number of remotes	3			
Lift Capacity at ball ends	2000			
Maximum Lift Capacity	2500			
AXLES				
Front	4WD			
Rear	Heavy Duty straight axle			
BRAKES				
Oil Immersed	•			
Hydraulic Multidisc	•			
OPERATOR ENVIRONMENT				
Tiltable Steering	NA			•
Operator Seat	•			
Flat Deck	•			
Suspended Brake	•			
2 Post foldable ROPS	◦			
Canopy	•			
DIMENSIONS & WEIGHT				
Wheel Base	2010	2145		2258
Overall Length	3875		4131	
Overall Width	1965	2087		
Height Top of ROPS	2538	2566	2589	
Height Top of Exhaust	2435	2464	2482	
Height Top of Steering Wheel	1763	1791	1814	
Ground Clearance	370	390	415	
Weight Standard Ballast	2740	2810		3250

• Standard ◦ Optional NA - Not available *Speed with standard tyres



caseih.com

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial Australia Pty Ltd reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2022 CNH Industrial Australia Pty Ltd. All rights reserved. Case IH, its respective logos and the red, black and grey colour scheme, as well as corporate and product identity used herein, are trademarks of CNH Industrial N.V. And may not be used without permission. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Printed in Australia. www.caseih.com 22CASEFARMALLLIFEPRO

CASE IH