



**SUPER
SERIES**

EMPOWERING *Asli Hero*
WITH THE ADVANCED TECHNOLOGY

THE ALL-NEW
3600-2 TX Super
49.5 HP
36.94 kW



Toll Free No.
1800 419 0124



Upgraded
FPT Engine



New Style



New Side
Silencer



Transmission
Heat Guard



Straight Axle
Planetary Drive
Rear Axle

**ASLI HERO KI
ASLI TAAQAT**

Model		NH 3600-2 - 2WD	NH 3600-2 -4WD
Engine	Engine Model	FPT S8000 series	
	Engine Type	4 Stroke Natural Aspirated Engine	
	Engine Power	36.94 kW (50 HP Cat.)	
	Rated RPM	2100	
Air Filter	Air Cleaner Type	Wet Type with Pre-cleaner	
	Clutch	Double Clutch with Independent Clutch Lever	
Transmission	Gear Box	8F+2R / 16F+4R* / 8F+8R* / 16F+16R*	
	Mechanical Shuttle	Optional	
PTO	Type	Independent, 6 Spline 540Std & Rev PTO EPTRAA (Optional)	
	RPM	540 @ 2016 540 E @ 1590 (Optional)	
Hydraulics	Maximum Lift capacity	1800 Kg. High Precision Hydraulic with ADDC	
	3 Point linkage	Cat-II	
Rear PTO	Type	Straight Axle Planetary Drive	
Brakes	Type	Real Oil Immersed Multi Disk Brake	
Steering	Type	Power Steering	
Tyre	Front	6.5-16 7.5-16 (Optional)	8.3-20 (Portal Axle) 9.5-24 (Industrial Axle)
	Rear	14.9-28 / 15.9-28 (Optional)	14.9-28 / 15.9-28 (Optional)
Electricals	Battery & Alternator capacity	88Ah Battery & 45 Amp Alternator	
Weight & Dimensions	Overall Length (mm)	3510	3610
	Width (mm)	1810	1810
	Height (mm)	2370	2370
	Wheelbase (mm)	2115	2040
	Ground Clearance (mm)	385	385
	Weight (kg)	1945	2145
Rear Tank	Fuel Tank Capacity (Litre)	55	55
Factory Fitted Options	Remote Valve		
	ROPS with Fiber Canopy		
	Rear Weight 1x32 Kg Each Side		
	Front Bumper / Front Weight Carrier		
	Stabilizer Bar		
	Potato Special Adjustable Front Axle		

*Optional

USAGE IN VARIOUS APPLICATIONS

Haulage



Field /Load Condition	Gear
• Easy on inclined track • Heavy Haulage	SH3 H3
• Moderate Load Haulage • High Speed operation	SH4 H4

Harrow/Cultivator



Field /Load Condition	Gear
• One Size Bigger Implement • Hard Soil, More Depth	SH1 L4
• Matching Implement, better productivity • H2 gear for faster work	H1 SH2

Chisel Plough/ Duck Foot Cultivator



Field /Load Condition	Gear
• Hard Soil, More Depth	SL4
• Light Soil, Moderate Depth	L4 SH1

Plough



Field Condition	Gear
• Hard Soil, More Depth	L3 SL4
• Light Soil, Moderate Depth	L4 SH1

Straw Reaper



Field Condition	Gear
• High moisture content straw	SL1 L1
• Low moisture content straw, more Productivity	SL2 L2 SL3

Rotavator



Field Condition	Gear
• Hard soil, Better Pulverization	SL1 L1
• Light Soil, better productivity	SL2 L2

CNH Industrial (India) Private Limited

Plot No. 03, Udyog Kendra, Greater Noida - 201306, District Gautam Budh Nagar, Uttar Pradesh

Note: New Holland believes in constantly working to bring improvements in their products. Therefore, the specifications given above may be changed without any prior notice. For latest information, contact your nearest dealership. The specifications given above are taken from the sub-clause of CFMTT1, Budni, Report/manufacturer's website/product leaflet.

Authorised Dealer

TOLL-FREE NO.
1800-419-0124
www.newholland.com/in

WORLD CLASS TRACTOR RANGE
20-110 HP

Leaflet/English/Sep/2025