Excavator Mulching Head



28" carbide tip bit limiting model

Transform your mini excavator into a forest clearing machine.

FOR USE ON: E42D and E50D mini excavators only

FEATURES:

- Compact body improves carrier balance
- Designed with heavier materials providing more torque keeping the rotor turning when other mulchers may stall
- Smooth cutting increases material flow while minimizing HP draw
- Effectively grinds up to 5" diameter material
- Rear throat maximizes productivity while sweeping along the ground
- Downward front discharge mitigates throat debris
- Standard double-tipped carbide cutting tools maximize performance and durability
- Durable components reduces the frequency of replacements and less repairs resulting in greater ROI of the mulcher



- Land clearing, site prep
- Right-of-way maintenance
- Parks and trails
- Wildfire break lines
- Gully, ravines, and hard to reach mulching locations
- Invasive species removal

Model	28" Excavator Mulcher Head
Part Number	92158029
Working Width	28" (711.2 mm)
Overall Width	40" (1016 mm)
Rotor Diameter	15" (381 mm)
Weight	750 lbs (340kg)
Flow Range GPM	12-40
Max Pressure PSI	4,000
Rotor Speed RPM	2,400
Rotor Style	Split Ring
# of Teeth	14
Max Material Diameter Size	5"
Case Drain	Yes
Mount Adapters: Cangini Coupler	Part No. 92158032
Mount Adapters: Werk-Brau	Part No. 92158031
Demolition Window Guard Required	Part No. 92158033
Dead Pin Kit	Part No. 92080147
Manufacturer	Fecon
Cutting Tools: Carbide Tool	Part No. 92158035

¹⁻Year standard product warranty through CNH Industrial for workmanship and defect not related to wear

PM-25319 Issued: 12/2025 Replaces: PM-24188

©2025 CNH Industrial America LLC. All rights reserved. New Holland and CNH Genuine Parts are trademarks in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC., are the property of those respective companies.



The machine needs to be configured with the Mulcher provision package (part no. 747275).

MULCHER PROVISION:†

- Choose 280kg counterweight or 420kg (instead of std. 50kg)
- Receive direct drain to tank (aka case drain)
- Receive an additional dedicated gear pump (14 gal/min or 53 l/min) to run the mulcher

[†]Note the mulcher provision doesn't increase the machine's overall GPM, rather it provides a constant, dedicated gear pump to run the mulcher



^{*}Mount Kits includes: Mount, hydraulic supply lines, case drain, hoses and quick disconnects