

STEIGER[®]





STEIGER® SERIES TRACTORS

7 Models | 425–715 | 467–778 Peak HP*

WHEELED

MODELS: 425 / 475 / 525 / 555 / 595 / 645

HORSEPOWER: 467 – 699 PEAK HP*

TRANSMISSION:

- PowerDrive Transmission
- CVXDrive Transmission: 425 / 475 / 525 / 555

CONFIGURATIONS:

- Row Crop Narrow-Frame, High-Horsepower or Heavy-Duty Wheeled Scraper

*See specs for details.

ROWTRAC

MODELS: 425 / 475 / 525

HORSEPOWER: 467 – 578 PEAK HP*

TRANSMISSION:

- PowerDrive Transmission or CVXDrive

CONFIGURATIONS:

- Ag Rowtrac

QUADTRAC

MODELS: 475 / 525 / 555 / 595 / 645 / 715

HORSEPOWER: 522 – 778 PEAK HP*

TRANSMISSION:

- PowerDrive Transmission
- CVXDrive Transmission: 475 / 525 / 555

CONFIGURATIONS:

- Ag Quadtrac or Heavy-Duty Quadtrac Scraper
- Optional Heavy-Duty Suspended Undercarriage

MODEL	425 WHEELED / ROWTRAC	475 WHEELED / ROWTRAC / QUADTRAC	525 WHEELED / ROWTRAC / QUADTRAC
POWER			
Engine Type	Tier 4 B/Final - Stage V		
SST Electronic Variable Turbo Charger	Wheeled, Rowtrac and Quadtrac		
TST Two-Stage Turbo Charger	N/A		
Engine HP ¹	425	475	525
Maximum Engine HP ²	467	522	578
PTO HP ³	409	462	516
Cylinders / Valves / Displacement	6 cyl. / 24 / 13L (787 cu. in.)		
ELECTRICAL			
Alternator / Battery / Battery Isolator	12V 240 amp standard (12V 330 amp optional) / three 950 cranking amps / Yes		
TRANSMISSION / PTO			
Standard	PowerDrive full-powershift 16F / 2R with 16 Hi (25 mph / 40 kph)	PowerDrive full-powershift 16F / 2R with 16 Hi (25 mph / 40 kph and 26.5 mph / 43 kph for Quadtrac models with HDS)	
Optional	CVXDrive CVT (25 mph / 40 kph)	CVXDrive CVT (25 mph / 40 kph and 26.5 mph / 43 kph for Quadtrac models with HDS)	
PTO Speed	1,000		
AXLES			
Axle Diameter (Wheeled / Rowtrac / Quadtrac)	5.0 in. (127 mm) bar with 4 gear planetary / Flanged / N/A	5.0 in. (127 mm) bar with 4 gear planetary / Flanged / Flanged	
Axle Width (Wheeled / Rowtrac / Quadtrac)	120 in. (3048 mm) / 80 in. (2032 mm) or 88 in. (2235 mm) or 120 in. (3048 mm) / N/A	120 in. (3048 mm) / 80 in. (2032 mm) or 88 in. (2235 mm) or 120 in. (3048 mm) / 88 in. (2235 mm)	
Wheelbase	148 in. (3 759 mm) / 160 in. (4 064 mm) / N/A	148 in. (3 759 mm) / 160 in. (4 064 mm) / 154 in. (3 912 mm)	
HYDRAULICS / HITCH			
Rear Remotes (Standard / Optional)	4 / up to 8		
Hydraulic Pump PowerDrive (Standard / Optional)	42 gpm (159 L/min.) / 57 gpm (216 L/min.)		
Hydraulic Pump CVXDrive	57 gpm (216 L/min.)		
Total Tractor Hydraulic Flow with Parallel/Twin Flow Pumps	113 gpm (428 L/min.)		
Available Flow at Single Remote Valve	35 gpm (132 L/min.)		
3-Point Hitch Category (Wheeled / Rowtrac / Quadtrac)	Cat. 4N* / Cat. 4N* / N/A	Cat. 4N* / Cat. 4N* / Cat. 4N	Cat. 4N / Cat. 4N* / Cat. 4N
Hitch Lift Capacity (Wheeled / Rowtrac / Quadtrac)	21,903 lb. (97.4 kN) / 21,903 lb. (97.4 kN) / N/A	21,903 lb. (97.4 kN) / 21,903 lb. (97.4 kN) / 22,250 lb. (10 092 kN)	
CAPACITIES			
Fuel Tank (Wheeled / Rowtrac / Quadtrac)	310 gal. (1 170 L) / 340 gal. (1 287 L) / N/A	310 gal. (1 170 L) / 340 gal. (1 287 L) / 470 gal. (1 779 L)	
Diesel Exhaust Fluid Tank (Wheeled / Rowtrac / Quadtrac)	42 gal. (159 L) / 42 gal. (159 L) / N/A	42 gal. (159 L) / 42 gal. (159 L) / 85 gal. (322 L)	
DIMENSIONS & WEIGHTS			
Drawbar (Standard / Option 1 / Option 2)	Cat. 4: 6,000 lb. (2 722 kg) / Cat. 4: 11,000 lb. (4 990 kg) / Cat. 5: 15,000 lb. (6 804 kg)		
Base: Max. Gross (Wheeled / Rowtrac / Quadtrac)	40,800 lb. (18 507 kg); 56,000 lb. (25 401 kg) / 52,200 lb. (23 678 kg); 60,000 lb. (27 215 kg) / 53,700 lb. (23 358 kg); 67,000 lb. (30 390 kg)		

¹Rated 2,100 engine rpm ISO per ECE R120 (CV) ²1,900 engine rpm ISO per ECE R120 (CV) ³1,000 PTO rpm ISO per ECE R120 (CV) –Power boost available during mobile PTO / hydraulics / transport operation * convertible to Cat. 3

MODEL	555 WHEELED / QUADTRAC	595 WHEELED / QUADTRAC	645 WHEELED / QUADTRAC	715 QUADTRAC
POWER				
Engine Type	Tier 4 B/Final - Stage V			
SST Electronic Variable Turbo Charger	NA			
TST Two-Stage Turbo Charger	Wheeled and Quadtrac			Quadtrac
Engine HP ¹	555	595	645	715
Maximum Engine HP ²	614	656	699	778
PTO HP ³	537			
Cylinders / Valves / Displacement	6 cyl. / 24 / 13L (787 cu. in.)			6-cyl. / 24 / 16L (970 cu. in.)
ELECTRICAL				
Alternator / Battery / Battery Isolator	12V 240 amp standard (12V 330 amp optional) / three 950 cranking amps / Yes			
TRANSMISSION / PTO				
Standard	PowerDrive full-powershift 16F / 2R with 16 Hi (25 mph / 40 kph and 26.5 mph / 43 kph for Quadtrac models with HDS)			PowerDrive full-powershift 16F / 2R with 16 Hi (26.5 mph / 43 kph)
Optional (Wheeled / Quadtrac)	CVXDrive CVT (25 mph / 40 kph and 26.5 mph / 43 kph for Quadtrac models with HDS)	N/A		
PTO Speed	1,000			
AXLES				
Axle Diameter (Wheeled / Quadtrac)	5.0 in. (127 mm) bar / Flanged	5.5 in. (140 mm) axle bar with 3 gear compound planetary / Flanged		N/A / Flanged
Axle Width (Wheeled / Quadtrac)	120 in. (3 048 mm) / 88 in. (2 235 mm)	120 in. (3 048 mm) / 88 in. (2 235 mm)		N/A / 88 in. (2 235 mm)
Wheelbase	154 in. (3 912 mm)			
HYDRAULICS / HITCH				
Rear Remotes (Standard / Optional)	4 / up to 8			
Hydraulic Pump PowerDrive (Standard / Optional)	42 gpm (159 L/min.) / 57 gpm (216 L/min.)			57 gpm (216 L/min.)
Hydraulic Pump CVXDrive	57 gpm (216 L/min.)	N/A		
Total Tractor Hydraulic Flow with Parallel/Twin Flow Pumps	113 gpm (428 L/min.)			
Available Flow at Single Remote Valve	35 gpm (132 L/min.)			
3-Point Hitch Category	Cat. 4N			
Hitch Lift Capacity (Wheeled / Quadtrac)	22,750 lb. (101.20 kN) / 22,250 lb. (10 092 kN)			N/A / 22,250 lb. (10 092 kN)
CAPACITIES				
Fuel Tank (Wheeled / Quadtrac)	455 gal. (1 722 L) / 470 gal. (1 779 L)			N/A / 520 gal. (1 968 L)
Diesel Exhaust Fluid Tank (Wheeled / Quadtrac)	66 gal. (250 L) / 85 gal. (322 L)			N/A / 85 gal. (322 L)
DIMENSIONS & WEIGHTS				
Drawbar (Standard / Option 1 / Option 2)	Cat. 4: 6,000 lb. (2 722 kg) / Cat. 4: 11,000 lb. (4 990 kg) / Cat. 5: 15,000 lb. (6 804 kg)			Cat. 5: 15,000 lb. (6 804 kg) / N/A / N/A
Base: Max. Gross (Wheeled / Quadtrac)	46,340 lb. (21 019 kg) : 60,000 lb. (27 216 kg) / 55,200 lb. (25 038 kg) : 67,000 lb. (30 390 kg)	50,328 lb. (22 828 kg) : 67,000 lb. (30 390 kg) / 56,800 lb. (25 764 kg) : 67,000 lb. (30 390 kg)		N/A / 61,200 lb. (27 760 kg) : 72,000 lb. (32 659 kg)

¹Rated 2,100 engine rpm ISO per ECE R120 (CV) ²1,900 engine rpm ISO per ECE R120 (CV) ³1,000 PTO rpm ISO per ECE R120 (CV) –Power boost available during mobile PTO / hydraulics / transport operation * convertible to Cat. 3

SAFETY NEVER HURTS![™] Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2024 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH24081401-REV

