

AXIAL-FLOW[®]

COMBINE HEADERS

SPECIFICATIONS



AXIAL-FLOW COMBINE HEADERS SPECIFICATIONS

CASE IH

CASE IH



AXIAL-FLOW COMBINE HEADERS

Corn Head | Grain Head | Pickup Head | Draper Head

DESIGNED TO MATCH THE CAPACITY OF AXIAL-FLOW COMBINES

Case IH header options deliver consistent performance and durability, regardless of crop or conditions, allowing you to harvest more of what you grow. Just like the combines behind them, Case IH headers are simple to set and adjust, intuitive to operate and help deliver the highest-quality grain to the hopper. With heads as wide as 61 feet, they deliver a steady stream of grain to match the high capacity of machines like the Axial-Flow AF series.



AXIAL-FLOW COMBINE HEADERS

Axial-Flow Combine Headers.....	4-5	Recommended Combine + Header Pairings.....	7
C500 Series Corn Head.....	6	Product Specifications.....	8-11
RowGuide Pro.....	6		



THE GREATEST CHOICE OF HEADS TO GIVE YOU THE GREATEST YIELDS

CORN HEADS

Case IH Corn Heads are designed to pick cleaner, harvest faster, grab more down corn and save more grain. The corn heads incorporate the latest innovations in harvest technology, with features that maximize your time in the field and minimize your yield loss.

Case IH 6 to 18 row corn heads—available in narrow or folding configurations—provide increased corn harvesting speeds and consistent chop lengths to help increase productivity without sacrificing chop quality.

GRAIN HEADS

The Case IH rigid auger grain head is designed to match the high horsepower combines of today, offering faster harvesting speeds and the adaptability to tackle different crop conditions effectively. It can handle a range of challenging situations, including tangled and downed crops as well as uneven terrains.



PICKUP HEADS

The Case IH pick up head is ideal for small-grain harvesting like cereal, grass seed, and more. Our simple, proven design helps minimize seed loss, while extra picking fingers and adjustable belt speeds allow for increased performance in tough conditions.

DRAPER HEADS

FD2 Series FlexDraper By MacDon offer both rigid and flexible cutterbar configurations, variable draper speeds, a wide range of cutting widths, and a head-first feeding design for unmatched harvesting efficiency.



C500 SERIES CORN HEAD

The C500 series corn head is designed to pick corn cleaner and faster while delivering exceptional downed corn performance and grain savings.

A spring-free, self-adjusting deck plate linkage system, an industry first, offers up to 6mm of optimal variation and its rubber-based design eliminates common buildup issues found in spring-adjusted alternatives, significantly reducing maintenance time and costs.

Independent drive lines for row unit and chopper drives with dedicated slip clutch protection ensure optimal performance and reduce the risk of damage to the entire drive system. Header-mounted automatic slip clutch detection utilizes in-cab alerts through the Pro 1200 or Pro 700 display to identify problems before a major failure occur.

The C512 and C516 feature the industry's largest auger offering higher capacity to align with the newly released AF series and 260 series combines, ensuring maximized capacity and throughput.

ROWGUIDE PRO

Experience the enhanced power and precision of new RowGuide Pro,[™] now optimized for the 260 & AF series combines. With significant improvements to the vehicle's hydraulics and steering systems, you'll enjoy a smoother, more responsive operation. RowGuide Pro removes manual corrections and interventions by combining GPS and advanced software for seamless row tracking, even in crop gaps like waterways. An enhanced steering system ensures smooth and efficient movement through the field. Elevate your harvesting performance with the latest advancements in agricultural technology.

RECOMMENDED COMBINE + HEADER PAIRINGS

CORN HEADS	SUB-MODEL	ROWS	SPACING (IN INCHES)	CONFIGURATION	5088	5130	5140	5150	6088	6130	6140	6150	6160	7088	7130	7140	7150	7160	7120	7230	7240	7250	7260	8120	8230	8240	8250	8260	9120	9230	9240	9250	9260	AF9 ¹	AF10 ¹	AF11 ¹		
					✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
C500 Series Corn Heads**	C508	8	30	Chopping / Non-chopping	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-	
	C512	12	20, 22, 30		-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	C516	16	20, 22, 30		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	C518	18	20, 22		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
4400 Series Corn Heads	4406	6	30, 36, 38	Chopping / Non-chopping	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	4408	8	30, 36, 38		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-
	4412	12	20, 22, 30		-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	4416	16	20, 22, 30		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	4418	18	20, 22		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
4400 Series Folding Corn Heads	4408	8	30	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-	
	4412	12	30	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
GRAIN HEADS	OVERALL WIDTH (IN FEET)			CONFIGURATION	5088	5130	5140	5150	6088	6130	6140	6150	6160	7088	7130	7140	7150	7160	7120	7230	7240	7250	7260	8120	8230	8240	8250	8260	9120	9230	9240	9250	9260	AF9	AF10	AF11		
Rigid Auger Head 2030	17, 20, 24, 30			Single Knife	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-		
Terraflex Auger Head 3020	20, 25, 30, 35				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
PICKUP HEADS	OVERALL WIDTH (IN FEET)			CONFIGURATION	5088	5130	5140	5150	6088	6130	6140	6150	6160	7088	7130	7140	7150	7160	7120	7230	7240	7250	7260	8120	8230	8240	8250	8260	9120	9230	9240	9250	9260	AF9	AF10	AF11		
Pickup Head 3016	12			1-piece belt	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
	15			3-piece belt	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
DRAPER HEADS	OVERALL WIDTH (IN FEET)			CONFIGURATION	5088	5130	5140	5150	6088	6130	6140	6150	6160	7088	7130	7140	7150	7160	7120	7230	7240	7250	7260	8120	8230	8240	8250	8260	9120	9230	9240	9250	9260	AF9	AF10	AF11		
Macdon FD2 Series FlexDraper	25, 30, 35, 40, 41, 45, 50, 61			Hydraulic cutting knife	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		

*Work with your local Case IH dealer for the best combine and header pairing for your operation. **The C500 series does not offer a folding configuration. ¹AF series when hooked to a 4400 series corn or prior to MY24 auger, draper and pick-up heads require lower retainer adapter kit.

4400 SERIES CORN HEADS	4406	4408	4408F	4412
GENERAL				
Divider Type	Hinged and floating			
Plastic	Yes			
Metal	No			
Number of Rows	6	8		12
Row Spacing	30 in. (762 mm) / 36 in. (914 mm) / 38 in. (965 mm)		30 in. (762 mm)	
Number of Gathering Chains	12	16		24
Type of Chain	Endless special chromed pins			
OVERALL DIMENSIONS				
Width (Max. Row Spacing)				
30 in. (762 mm)	16 ft. (4870 mm)	21 ft. (6394 mm)		31 ft. (9442 mm)
36 in. (914 mm)	18 ft. 8 in. (5682 mm)	24 ft. 8 in. (7511 mm)	N/A	
38 in. (965 mm)	19 ft. 2 in. (5836 mm)	25 ft. 6 in. (7766 mm)	N/A	
Height (Level Ground)	4 ft. 2 in. (1258 mm)			
Length with Dividers	9 ft. 11 in. (3010 mm)			
Length without Dividers	7 ft. 6 in. (2272 mm)			
WEIGHTS				
Approximate Weight — Non Chopping Header				
30 in. (762 mm)	3,988 lb. (1809 kg)	5,484 lb. (2488 kg)	6,726 lb. (3051 kg)	8,058 lb. (3655 kg)
36 in. (914 mm)	4,288 lb. (1945 kg)	5,837 lb. (2648 kg)	N/A	
38 in. (965 mm)	4,290 lb. (1946 kg)	5,842 lb. (2650 kg)	N/A	
Chopping Units Additional Weight	Add an additional 75 lb. per row			
ROW UNITS				
Point-to-Point Knife Type Stalk Rolls	Standard			
Number of Knives per Roll	4 - single edge			
Weed Knives (Single Piece)	Adjustable			
Row Unit Drive	Enclosed in gearbox – spur/bevel gears			
Stalk Roll Length	23.4 in. (594 mm)			
Stalk Roll Diameter	4.25 in. (108 mm)			
Stalk Roll Speed (Nominal)	1,058 rpm			
Gathering Chain Speed (Nominal)	349 fpm			
SLIP CLUTCHES				
Row Units	1 per row radial pin			
Auger Drive	1 per auger radial pin			
STRIPPER PLATES				
Hydraulic	Hydraulic adjustable			
Stalk Stompers (Available Through Part Marketing)	Optional			
Automatic Front Height Control/Lateral Tilt	Optional/pre-wired in main harness			
HEADER DATA				
Header Jackshaft Speed				
4400 CH on 7010/8010/20 Series	575 rpm			
Auger Diameter	15.75 in. (400 mm)			
Auger Tube Dimension	6.3 in. (160 mm)			
Flighting Pitch	19.7 in. (500 mm)			
Reverse Flighting	No			

4400 SERIES CORN HEADS	4412 NARROW ROW	4412F	4416	4416 NARROW ROW	4418 NARROW ROW
GENERAL					
Divider Type	Hinged and floating				
Plastic	Yes				
Metal	No				
Number of Rows	12			16	18
Row Spacing	20 in. (508 mm) / 22 in. (559 mm)	30 in. (762 mm)		20 in. (508 mm) / 22 in. (559 mm)	
Number of Gathering Chains	24			32	36
Type of Chain	Endless special chromed pins				
OVERALL DIMENSIONS					
Width (Max. Row Spacing)					
20 in. (508 mm)	22.1 ft. (9442 mm)	N/A		27.8 ft. (8484 mm)	31.2 ft. (9500 mm)
22 in. (559 mm)	23 ft. (7010 mm)	N/A		30.3 ft. (9246 mm)	34 ft. (10363 mm)
30 in. (762 mm)	N/A	30 ft. 11 in. (9410 mm)	42.5 ft. (12954 mm)	N/A	
36 in. (914 mm)	N/A			N/A	
38 in. (965 mm)	N/A			N/A	
Height (Level Ground)	4 ft. 2 in. (1258 mm)	4 ft. 7 in. (1338 mm)	4 ft. 2 in. (1258 mm)		
Length With Dividers	9 ft. 4 in. (2870 mm)	9 ft. 11 in. (3010 mm)		9 ft. 4 in. (2870 mm)	
Length Without Dividers	7 ft. 9 in. (2405 mm)	7 ft. 6 in. (2272 mm)		7 ft. 9 in. (2405 mm)	
WEIGHTS					
Approximate Weight					
20 in. (508 mm) Standard/Chopping	7,231 lb. (2725 kg)/ 7,931 lb. (3597 kg)	N/A	N/A	7,860 lb. (3535 kg)/ 9,363 lb. (4217 kg)	8,697 lb. (3915 kg)/ 10,469 lb. (4719 kg)
22 in. (559 mm) Standard/Chopping	7,360 lb. (2774 kg)/ 8,530 lb. (3869 kg)	N/A	N/A	8,145 lb. (3665 kg)/ 9,944 lb. (4481 kg)	8,820 lb. (3971 kg)/ 10,646 lb. (4799 kg)
30 in. (762 mm)	N/A	9,686 lb. (4393 kg)	11,515 lb. (5223 kg)	N/A	
36 in. (914 mm)	N/A				
38 in. (965 mm)	N/A				
Chopping Units Additional Weight	Add an additional 75 lb. per row				
ROW UNITS					
Point-to-Point Knife Type Stalk Rolls	Standard				
Number of Knives per Roll	4 - single edge				
Weed Knives (Single Piece)	Adjustable				
Row Unit Drive	Enclosed in gearbox – spur/bevel gears				
Stalk Roll Length	23.4 in. (594 mm)				
Stalk Roll Diameter	4.25 in. (108 mm)				
Stalk Roll Speed (Nominal)	1,062 rpm	1,058 rpm		1,062 rpm	
Gathering Chain Speed (Nominal)	348 fpm	349 fpm		348 fpm	
SLIP CLUTCHES					
Row Units	1 per row radial pin				
Auger Drive	1 per auger radial pin				
STRIPPER PLATES					
Hydraulic	Parallel linkage; hydraulic adjustable	Hydraulic adjustable		Parallel linkage; hydraulic adjustable	
Stalk Stompers (Available Through Part Marketing)	Optional				
Automatic Front Height Control/Lateral Tilt	Optional/pre-wired in main harness				
HEADER DATA					
Header Jackshaft Speed					
4400 CH On 7010/8010/20 Series	575 rpm				
Auger Diameter	15.75 in. (400 mm)				
Auger Tube Dimension	6.3 in. (160 mm)				
Flighting Pitch	19.7 in. (500 mm)				
Reverse Flighting	No				

GRAIN HEADERS	2030 RIGID AUGER HEADER	3020 FLEXIBLE AUGER HEADER
CUTTER BAR		
Cutting Widths	17, 20, 24, 30 ft. (5.1, 6.1, 7.62, 9.14 m)	20, 25, 30, 35 ft. (6.1, 7.62, 9.14, 10.6 m)
WEIGHT – APPROX.		
17 ft. (5.1 m)	2,998 lb. (1 360 kg)	4,242 lb. (1 924 kg)
20 ft. (6.1 m) / 21 ft. (6.4 m)	3,351 lb. (1 520 kg)	4,242 lb. (1 924 kg)
24 ft. (7.3 m)	3,880 lb. (1 760 kg)	N/A
25 ft. (7. m)	N/A	5,302 lb. (2 405 kg)
30 ft. (9.1 m)	4,982 lb. (2 260 kg)	6,362 lb. (2 886 kg)
35 ft. (10.6 m)	N/A	6,760 lb. (3 066 kg)
40 ft. (12.2 m)	N/A	N/A
45 ft. (13.7 m)	N/A	
AUGER		
Diameter	24 in. (610 mm)	26 in. (660 mm)
Speed	Std. 178 rpm/Opt. 152 rpm	Std. 147 rpm/Opt. 164 rpm
Full Fingered	Standard	Standard 25, 30 and 35 ft.
REEL		
Reel	6 bat	6 bat
Pickup Reel (Tines)	Plastic	6 (plastic)
Diameter	42 in. (1 067 mm)	
Drive	Hydraulic / 12 to 60 rpm	Hydraulic / 5 to 61 rpm
SICKLE/KNIFE		
Type	Overserrated “sta-sharp”/ “super sta-sharp”	
Drive	Section to wobble box	
Knife	Std. 3 in. (76.2 mm)	

PICKUP HEADERS	3016 GRASS SEED SPECIAL	3016 GRAIN
FLOATING AUGER		
Actual Pickup Widths	12 ft. (3.7 m)	15 ft. (4.6 m)
Diameter	26 in. (660 mm)	26 in. (660 mm)
Speed	187 rpm (160 Opt)	187 rpm (160 Opt)
PICK-UP		
Drive – RPM	Hydraulic	
Wind Guard Lift	Hydraulic	
WEIGHT WITH BELT PICKUP		
12 ft. (3.7 m) Width	3,090 lb. (1 401 kg)	N/A
15 ft. (4.6 m) Width	N/A	3,180 lb. (1 442 kg)
DRAPER BELTS – 19 IN. (48.3 CM)		
14 ft. (4.27 m) Width	8	8
16 ft. (4.9 m) Width		10
WIDTH		
Overall Width to Tire Edges	13.5 ft. (4.11 m)	16.5 ft. (5.0 m)

FD2 FLEXDRAPER® BY MACDON*	FD225	FD230	FD235	FD240	FD241	FD245	FD250	FD261
CUTTER BAR								
Cutting Width	25 ft. (7.6 m)	30 ft. (9.1 m)	35 ft. (10.6 m)	40 ft. (12.2 m)	41 ft. (12.5 m)	45 ft. (13.7 m)	50 ft. (15.2 m)	61 ft. (18.6 m)
WEIGHT**								
Single Knife Drive without FM200	5016 lb. (2 276 kg)	5851 lb. (2 655 kg)	6311 lb. (2 863 kg)	6495 lb. (2 947 kg)				
Double Knife Drive without FM200			6487 lb. (2 943 kg)	6759 lb. (3 063 kg)	7136 lb. (3 238 kg)			
Double Knife Drive with Triple Reel without FM200				7079 lb. (3 212 kg)	7912 lb. (3 590 kg)	8382 lb. (3 803 kg)	8798 lb. (3 991 kg)	
KNIFE								
Type / Drive / Speed	Single or Double knife / Hydraulic, MacDon design enclosed oil bath knife drive box(es) / 1200-1400/1500 spm, varies depending on header size							
REEL								
Type / Drive / Speed / Fingers	Pick-up reel, five bats, one-piece (single),two-piece (double) or three-piece (triple), flip-over design, cam-leading finger control / Hydraulic / 0 to 67 rpm (varies depending on combine model) / 11.4" (290 mm) length, wear-resistant HD plastic, 4" (102 mm) spacing							
CONVEYOR								
Type / Drive / Speed	50" (1 270 mm) deep, reversible, rubber skim-coated drapers, double V-guide with tracking, integral seal on leading edge / 0 to 209 m/min (0 to 687 ft./min)							
GENERAL								
Guard Types Available	ClearCut™ Pointed Guards - Forged and Double Heat Treated (DHT) with Forged, Single Bolt Adjustment Hold-Down; ClearCut™ PlugFree™ Short Guards - Forged and Double Heat Treated (DHT) with Forged, Dual Bolt Adjustment Hold-Down							
Standard Features	Fits most current model combines, hydraulic fore-aft reel positioner, hydraulic header tilt, in-cab side draper speed control, cutterbar poly wear plates, auto-header height with header angle and ground pressure indicators							
Field-Installed Options***	EasyMove™ Transport System, ContourMax™ Contour Wheels, Upper Cross Auger, VertiBlade™ Vertical Knife, stabilizer wheels, lateral tilt automatic header height control, Sunflower attachment							

C500 SERIES CORN HEADS	C512-20	C512-22	C516-20	C516-22	C518-20	C518-22	C508-30	C512-30	C516-30
GENERAL									
Number of Rows	12	12	16	16	18	18	8	12	16
Row Spacing	20" or 22"						30"		
Number of Gathering Chains	24		32		36		16	24	32
Type of Chain	Endless special chromed pins								
OVERALL DIMENSIONS									
Max Width	253 in. (6,420 mm)	275 in. (6,979 mm)	333 in. (8,452 mm)	364 in. (9,238 mm)	373 in. (9,469 mm)	407 in. (10,333 mm)	247 in. (6,254 mm)	366 in. (9,289 mm)	487 in. (12,360 mm)
Height Ground Level	52 in. (1,308 mm)	52 in. (1,308 mm)	52 in. (1,308 mm)	52 in. (1,308 mm)	52 in. (1,308 mm)	52 in. (1,308 mm)	52 in. (1,308 mm)	55 in. (1,391 mm)	55 in. (1,391 mm)
Length (Dividers Down)	113 in. (2,879 mm)	113 in. (2,879 mm)	113 in. (2,879 mm)	113 in. (2,879 mm)	113 in. (2,879 mm)	113 in. (2,879 mm)	113 in. (2,879 mm)	121 in. (3,086 mm)	121 in. (3,086 mm)
Length (Dividers Up)	86 in. (2,186 mm)	86 in. (2,186 mm)	86 in. (2,186 mm)	86 in. (2,186 mm)	86 in. (2,186 mm)	86 in. (2,186 mm)	86 in. (2,186 mm)	96 in. (2,433 mm)	96 in. (2,433 mm)
WEIGHTS									
Non-Chopping	6,560 lb. (2 976 kg)	6,660 lb. (3 021 kg)	8,170 lb. (3 706 kg)	8,750 lb. (3 969 kg)	8,790 lb. (3 987 kg)	9,010 lb. (4 087 kg)	5,260 lb. (2 386 kg)	8,080 lb. (3 665 kg)	10,490 lb. (4 758 kg)
Chopping	7,730 lb. (3 506 kg)	7,800 lb. (3 538 kg)	9,780 lb. (4 436 kg)	10,370 lb. (4 704 kg)	10,530 lb. (4 776 kg)	10,770 lb. (4 885 kg)	6,480 lb. (2 939 kg)	9,740 lb. (4 418 kg)	12,530 lb. (5 684 kg)
ROW UNITS									
Point-to-Point Knife Type Stalk Rolls	Standard								
Number of knives per roll	4 - single edge								
Weed knives (single piece)	Adjustable								
Row Unit Drive	Full gearbox drive								
Chopper Drive (optional)	Full gearbox drive								
Stalk Roll Length	19.25 in. (488 mm)								
Stalk Roll Diameter	4.25 in. (108 mm)								
Stalk Roll Speed (Nominal)	1061.5 RPM								
Gathering Chain Speed (Nominal)	440 RPM								
SLIP CLUTCHES									
Row Unit Gearboxes	1 per gearbox - radial pin design								
Chopper Gearboxes (if equipped)	1 per gearbox - radial pin design								
STRIPPER PLATES									
In-cab hydraulic control	Standard								
Spring-free self-adjusting feature	Standard								
HEADER DATA									
Auger Diameter	15.75 in. (400 mm)						23.6 in. (600 mm)		
Auger Tube Dimension	6.3 in. (160mm)						10.75 in. (273 mm)		
Flighting Pitch	19.7 in. (500 mm)						24.6 in. (625 mm)		
Reverse Flighting	No						Yes		



f v X @ in
caseih.com

SAFETY NEVER HURTS!TM Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2024 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH24081502

CASE IH