

# FARMALL® COMPACT A

MODELS: 35A/40A/45A/50A/55A

SPECIFICATIONS

FARMALL COMPACT A SPECIFICATIONS

CASE 



CASE 



| MODEL                                                 | FARMALL 35A                                              | FARMALL 40A                              | FARMALL 45A                                          | FARMALL 50A | FARMALL 55A |
|-------------------------------------------------------|----------------------------------------------------------|------------------------------------------|------------------------------------------------------|-------------|-------------|
| Operator Station                                      | Non-cab                                                  |                                          |                                                      |             |             |
| Traction                                              | MFD                                                      |                                          |                                                      |             |             |
| ENGINE                                                |                                                          |                                          |                                                      |             |             |
| Type                                                  | 3-cylinder, Tier 4 B/Final                               | 3-cylinder, Tier 4 B/Final, turbocharged |                                                      |             |             |
| Displacement                                          | 114.7 cu.in. (1.9 L)                                     |                                          |                                                      |             |             |
| Engine HP¹                                            | 35                                                       | 40                                       | 47                                                   | 52          | 57          |
| PTO HP¹ (Mechanical Trans./Hydrostatic Trans.)        | 31.0/30.1                                                | 35.9/34.8                                | 40.6/38.3                                            | 45.0/42.4   | 49.3/46.4   |
| Rated Engine RPM                                      | 2,600                                                    |                                          |                                                      |             |             |
| TRANSMISSION                                          |                                                          |                                          |                                                      |             |             |
| Standard                                              | 12×12 Mechanical shuttle with synchro shift (dry clutch) |                                          |                                                      |             |             |
| Optional                                              | 3-range Hydrostatic                                      |                                          | 3-range Servo-Hydrostatic                            |             |             |
| Differential Lock                                     | Mechanical                                               |                                          |                                                      |             |             |
| MFD Engagement                                        | Electro-Hydraulic                                        |                                          |                                                      |             |             |
| PTO Speed (Standard/Optional)                         | 540/N/A                                                  |                                          |                                                      |             |             |
| AXLES                                                 |                                                          |                                          |                                                      |             |             |
| Front                                                 | Mechanical Front Drive (MFD)                             |                                          |                                                      |             |             |
| Rear                                                  | Flanged                                                  |                                          |                                                      |             |             |
| Turning Radius (Without Brakes)                       | 10.5 ft. (3.2 m)                                         |                                          | 10 ft. (3.1 m)                                       |             |             |
| Turning Radius (With Brakes)                          | 9 ft. (2.7 m)                                            |                                          | 9.5 ft. (2.9 m)                                      |             |             |
| HYDRAULICS/HITCH                                      |                                                          |                                          |                                                      |             |             |
| Type                                                  | Open Center                                              |                                          |                                                      |             |             |
| Rear Remotes (Standard/Optional)                      | 0/3                                                      |                                          |                                                      |             |             |
| Implement Pump Flow                                   | 8.4 gpm (31.8 L)                                         |                                          | 9.9 gpm (37.5 L)                                     |             |             |
| Total Flow                                            | 13.3 gpm (50.5 L)                                        |                                          | HST: 16.9 gpm (64.1 L)/Mechanical: 15.5 gpm (58.9 L) |             |             |
| 3pt Hitch Category and Draft Sensing Type             | 1, Mechanical Draft Control (MDC)                        |                                          |                                                      |             |             |
| Lower Link End/Stabilizer Type                        | Fixed ends/Telescopic stabilizers                        |                                          |                                                      |             |             |
| Lift Capacity @ 24 in. Behind Pin (Standard/Optional) | 1,596 lb. (724 kg)/N/A                                   |                                          | 2,310 lb. (1 048 kg)/N/A                             |             |             |
| CAPACITIES                                            |                                                          |                                          |                                                      |             |             |
| Fuel Tank                                             | 12.6 gal (48 L)                                          |                                          | 12.4 gal (47 L)                                      |             |             |
| Diesel Exhaust Fluid Tank                             | No DEF required                                          |                                          |                                                      |             |             |
| DIMENSIONS & WEIGHTS                                  |                                                          |                                          |                                                      |             |             |
| Wheelbase                                             | 66.2 in. (1 682 mm)                                      |                                          | 74.7 in. (1 896.7 mm)                                |             |             |
| Overall Length                                        | 119.4 in. (3 033 mm)                                     |                                          | 125.7 in. (3 192 mm)                                 |             |             |
| Minimum Height (ROPS Folded)                          | 74.2 in. (1 884 mm)                                      |                                          | 74.3 in. (1 887.5 mm)                                |             |             |
| Overall Height (Top of ROPS)                          | 96.2 in. (2 444 mm)                                      |                                          | 99 in. (2 513.5 mm)                                  |             |             |
| Weight                                                | 3,042 lb. (1 380 kg)                                     | 3,053 lb. (1 385 kg)                     | Gear: 3,015 lb. (1 368 kg)/HST: 3,037 lb. (1 378 kg) |             |             |

<sup>1</sup> At rated engine RPM.

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2026 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com C1H26081801

