



- Scan issue functionality for severe faults and low fuel Customized notifications and alerts
- SNOITAJIITON AVITJAOA9 HTIW GAMAOANI YAT2

Analyze specific areas within a field for additional

View agronomic data layers for specific fields year

Monitor task completion and manage different crop

Track exact location and activities of each machine

after year, with no risk of losing them

ТЭЭЛЭ ЭЛОНЖ ЯООҮ ЯОТІИОМ ДИА ЭДАИАМ

ATAD JIMONOAÐA AUOY JZIJAUZIV

- Filtering Capabilities: Quickly access specific machines the app to learn key teatures and tips.

consequential damage.

- Guided Onboarding: New users are guided through .9mit-lest ni sutsts snidosm
- Real-Time Monitoring: Monitor task completion and

notifications and alerts to prevent major wear or

operators through remote display sessions.

and make near real-time adjustments.

adjustments from any location.

Enhanced Coordination: Improve coordination with

Proactive Notifications: Stay informed with customized

Real-Time Adjustments: Provide guidance to operators

view machine parameters and cameras, making

Remote Display Viewing (RDV): Use RDV to

MAXIMIZED EFFICIENCY WITH FIELDOPS MOBILE

or fields with the app's filtering capabilities.

- SIMPLIFIED AGRICULTURAL OPERATIONS
- activities of each machine in your fleet. Track Machine Activities: Track the exact location and
- .9lidoM resources, locations, and customers with FieldOps
- Comprehensive Management: Manage different crops, interface.
- machines, fields, and activities with an optimized User-Friendly Interface: Navigate easily through
- on iOS and Android platforms. Available on iOS and Android: Access FieldOps Mobile
- тиэмэдаиам мяая дэрианиэ
- - on the go
 - Farm management








case III FieldOps


Streamlined Workflow with Case IH FieldOpsTM

Case IH FieldOps is the new farm management app



stugisni

plan, and analyze all your farming operations. With a designed to simplify and enhance the way you monitor,



II ISVO

MANAGE. MIEM **CONNECT.**

WE EXIST TO SERVE FARMERS

Their challenges. Their demands. Their goals. Meeting them is our purpose. And we will settle for nothing less than ensuring their continued success.



Free phone: 00 800 22 73 44 00

Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illus-trations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard

equipment. Case IH recommends AKCELA lubricants. TP01 / SM / 02.25 / Printed in Italy Cod.No. 25MEAC8001INB

 $f \odot \otimes 0$ in

caseih.com





anticipating their needs to help them achieve more than they ever imagined possible.



The world is powered by agriculture. Farmers produce the food, fibre and fuel that supports nearly every aspect of life. Our mission at Case IH is to support these men and women with innovative, reliable and efficient solutions to meet the demands of modern farming. We are the brand for professional producers — a partner in their productivity,







THE NEXT LEVEL PUNA 220 GVXDRIVE

Designed with you

The demands of business require efficient technology



more uptime in the field. The new Puma AFS Connect offers all of this with while keeping operating costs in check was the answer. more power, more comfort and more automation - betnew uov terk beake ewe asked what you wanted to stay productive and profitable. When we started

Austoft 4000 is designed to harvest crops up to 85 tonnes increased productivity in subsequent ration crops. The

significantly increases the machine's cost-benefit. Case IH sugarcane harvester models. This characteristic harvesters, many of its parts are interchangeable with other with the same tunctional concept as the Austoft /000 Series models and is easy to move between cane fields. Designed The Austoft 4000 is smaller in size compared to conventional

easily accessible, streamlining the machine's maintenance, The engine, hydraulic system, and industrial components are The Austoft 4000 was designed to make maintenance simple.

convenience and functionality for the operator during the long The controls are ergonomically positioned to ensure for the operator, has good visibility and easy to operate. For greater productivity, the Austoff 4000 is comfortable is compact, light, has excellent manoeuvrability and an compacting the root zone of the adjacent cane row. It 4000 is narrow enough to harvest one row without Working in row spacings from 1.2 meters, the Austoft

SUGARCANE FIELD BETTER CUTTING QUALITY AND LONGER STOOL LIFE IN THE

capacity, creating a significant gain in machine productivity. such as the Austoff 9000 series, to harvest to their full productivity soils. This frees the bigger volume harvesters, plantations, where it can harvest short rows and/or low harvesting mechanically, as well as those with large The Austoft 4000 is a superb option for cane growers

from 1.2 up to 1.5 meters. demonstrates its versatility by harvesting fields with spacings Designed for maximum performance, the Austoft 4000 **MORE VERSATILITY**

use reduced row spacings from 1.2 to 1.5 meters. to streamline the harvesting process in sugarcane fields that The Case IH Austoft 4000 is a compact harvester, designed

and improved sugarcane harvester. ethanol sector, is launching the Case IH Austoft 4000, a new Case IH, committed to the evolution of the global sugar and

excellent base cut, resulting in reduced cane loss and row spacing to make its proven cutting technology available everywhere. Sugar cane harvesting is part of the Case II DNA, Austoft 4000 provides an efficient solution for sugar cane plantation, with reduced

When best in Class cutting quality meet excellent cost-benefit

SUGAR CANE HARVESTER 0004 T70T2UA







Norking hours.

SOMFORT FOR THE OPERATOR

EASY & FAST TO SERVICE

EXCELLENT COST-BENEFIT

per hectare.

which in turn increases it's availability.

CASE IH FOR THOSE WHO DEMAND MORE

STEIGER / QUADTRAC

12 models from 425 to 715 hp PUT A MASTER OF PRODUCTIVITY IN YOUR FIELD

- STEIGER 425, 475, 525, 555, 595 & 645 QUADTRAC 475, 525, 555, 595, 645 & 715
- Customized for tillage, planting, seeding, land leveling and tile plow operations
- Powered by a high pressure common rail 13 & 16 litres-FPT engine featuring a two-stage turbo, Tier 2 emission level
- Up to 743 hp maximum boosted power 16x2 Full Powershift
- Up to 428 I/min max. hydraulic pump flow
- Up to 8 rear remote valves Fuel saver Automatic Productivity
- Management (APM) ■ Quadtrac – exclusive 4 tracks system for
- minimum soil compaction
- Scraper version for scraping applications AccuGuide precision guidance, Telematics and ISOBUS



4 models with 75 to 110 hp MULTI TASKING FLEXIBILITY

FARMALL 75JX, FARMALL 90JX,

- FARMALL 100JX, FARMALL 110JX Available with Cabin or with ROPS, 4WD
- Turbocharged and intercooler mechanical injection, Tier 3 engine
- Optional Hydraulic Power Shuttle
- Optional factory fitted front loader
- Factory fitted front loader ■ Up to 4,700 kg lift capacity
- 110 litre fuel tank capacity



MAGNUM ROWTRAC

4 models from 355 to 405 hp TURNS LIKE WHEELS, FLOATS LIKE TRACKS

MAGNUM 355. 405 PWRDRIVE ROWTRAC MAGNUM 355, 385 CVXDRIVE ROWTRAC

- Proven track design to protect your soil and increase your pulling capacity
- Various Axle spacing options available to adapt to your crop in program
- Up to 435 hp maximum boosted power Powered by a high pressure common rail
- 8.7 litres-FPT engine, Tier 2 emission level Full Power Shift and CVT continuously variable
- transmission Fuel saver Automatic Productivity Management (APM)
- Up to 328 I/min max. hydraulic pump flow AccuGuide precision guidance, Telematics and ISOBUS





FARMALL JXM

2 models from 80 to 90 hp HIGH VERSATILITY, HIGH RELIABILITY

FARMALL 80JXM, 90JXM

- Flat deck, ROPS, 2WD/4WD Turbocharged and intercooler mechanical injection,
- Tier 3 engine Optional Hydraulic Power Shuttle
- Heavy duty straight rear axle
- 54 I/min open-centre hydraulic system
- 90 litre fuel tank capacity ■ Up to 3,500 kg lift capacity



AXIAL-FLOW COMBINES

8 models from 210 to 625 hp HARVEST YOUR SUCCESS



AXIAL-FLOW 5150

- Engine Tier 3 NEF 6.7 litres
- Grain Tank 9,200 litres Unloading rate 88 l/s

AXIAL-FLOW 6150

- Engine Tier 3
- Cursor 9 (8.7 litres) Grain Tank 10,570 litres
- Unloading rate 113 l/s
- AXIAL-FLOW 7150 Engine Tier 3
- Cursor 9 (8.7 litres) Grain Tank 10,570 litres
- Unloading rate 113 l/s

AXIAL-FLOW 7250 Engine Tier 2

- Cursor 11 (11.1 litres)
- Grain Tank 11,100 or 14,400 litres
- Unloading rate 113 or 141 l/s

HEADERS The greatest choice of headers to give you the greatest yields

AXIAL-FLOW 4088

Engine Tier 3

NEF 6.7 litres

AXIAL-FLOW 4099

Engine Tier 3

NEF 6.7 litres

Grain Tank 6,000 litres

Grain Tank 6,500 litres

Unloading rate 63 l/s

Unloading rate 63 l/s






1 model with 373 hp MAXIMIZE PICKING EFFICIENCY

COTTON EXPRESS 630









AXIAL-FLOW 8250 Engine Tier 2

 Cursor 13 (12.9 litres) Grain Tank 14,400 litres Unloading rate 113 or 159 l/s

AXIAL-FLOW 9250

- Engine Tier 2

- Cursor 16 (15.9 litres)
- Grain Tank 14,400 litres ■ Unloading rate 113 or 159 l/s









- planting window PRECISELY WHAT YOU NEED
- **2000 SERIES PLANTERS** Rows 12, 16 and 24 Spacing 30 in. (76.2 cm)



3 models from 176 to 415 hp

PIONEERING REFERENCE AND LEADERSHIP IN THE SUGAR AND ETHONOL MARKET

AUSTOFT 4000 Cummins 5.8 litres / wheels ■ Suitable from 1.2 m row spacing

- AUSTOFT 9000 Cursor 11 (11.1 litres) / wheels
- Suitable from 1.5 m row spa
- AUSTOFT 9900 Cursor 11 (11.1 litres) / tracks
- Suitable from 1.5 m row spacing Double Alternate version available

- FARMLIFT 1 models at 129 hp TAKE BUSINESS TO NEW HEIGHTS
- Stage 3B 4 Cylinders 4.485 cm³
- Up to 4,200Kg Lift Capacity 7m lift height capacity 160 I/min CCLS Pump

MAGNUM

10 models from 265 to 405 hp BIG PERFORMANCE. HIGH VALUE



PUMA / PUMA CVT

8 models from 142 to 220 hp EFFICIENT POWER FOR PROFITABLE FARM

- PUMA 185, 200, 220 POWERDRIVE AND CVXDRIVE Powered by a high pressure common rail 6 cylinder,
- 6.7 litres FPT engine, Tier 3 emission level ■ Up to 260 hp maximum boosted power
- 18x6/19x6 Full Power Shift or CVT continuously variable transmission
- AccuGuide precision guidance and ISOBUS connectivity
- 120/150 litre CCLS pump
- PUMA 140, 155
- Powered by a high pressure common rail 6 cylinder, 6.7 litres FPT engine, Tier 3 emission level
- Up to 193 hp maximum boosted power ■ 18x6 or 19x6 Semi Powershift/Full Powershift
- transmission AccuGuide precision guidance and ISOBUS
- connectivity ■ 113 litre CCLS pump



JX STRADDLE

3 models from 80 to 98 hp POWER, PERFORMANCE AND TOUGHNESS

■ Fuel saver Automatic Productivity Management (APM)

AccuGuide precision guidance, Telematics and ISOBUS

- JX80, JX90, JX95 STRADDLE Straddle, ROPS, 2WD/4WD
- Mechanical injection, Tier 2 engine
- Mechanical Shuttle



SUGAR CANE HARVESTERS



PRECISION DISK 500T AIR DRILL

Features an on-board mounted tank with seed metering, section overlap control, and unmatched maneuverability. Available in 30 and 40 ft toolbar widths.

PRECISION DISC DRILLS ■ Toolbar width: 30-40 ft Transport height: 13-13,8ft (3,96-4,2m) Transport width: 12.5-18.5 ft (3.84-5.63 m) Road-to-opener clearance: 8.5 in (21.6 cm) Weight (empty): 19,000-26,500 lbs (8,700-12,020 kg)

SELF-PROPELLED WINDROWERS

1 model 186 hp

Engine Tier 3 - 6 cylinder Dual Speed Hydrostatic 0 - 39 kph



SMALL SQUARE BALERS

Model flow type



LARGE SQUARE BALERS 11 models - 3 sizes of bales

LB XL, XLD & HD

Bale dimensions (cm) 80 x 90 / 120 x 70 / 120 x 90

- Pick-up width: 2.00 / 2.23 / 2.35m Feeding type: packer / packer cutter rotor cutter
- High Density version on 120x90 models



Cutting width 1.67 - 3.16 m


From 4 and 8 discs

7 models mounted and pull-type MD, MDX & TD SERIES

DISC MOWER CONDITIONERS 4 models side pull or center pivot

DC SERIES Cutting width 2.80 - 4.90 m From 7 and 10 discs Flail, steel or rubber condition

WHEEL RAKES 6 models trailing and carted WR SERIES



ROUND BALERS 5 models rotor feeder - 6 rotor cutter **RB344 FIXED CHAMBER** Bale dimensions (cm): 120 x 125 Pick-up: width 2.00 m

 Rotor Feeder / Rotor Cutter Net or Twine wrapping

RB455 - 465 VARIABLE CHAMBER Bale dimensions (cm): 120 x from 90 to 180 Pick-up: width 2.05 or 2.35 m

- OSF / Rotor Feeder / Rotor Cutter Net or Twine wrapping
- RB456 466 VARIABLE CHAMBER Bale dimensions (cm): 120 x from 90 to 190
- Pick-up: width 2.30 m Rotor Feeder / Rotor Cutter Net wrapping
- **RB545 FIXED CHAMBER**
- Bale dimensions (cm): 122 x 125 Pick-up: width 2.20 m
- Rotor Cutter / Silage pack Plastic or Net Wrapping

■ 3.4 to 8.3 m working width

TRUE-TANDEM DISK HARROWS

- single or double fold
- waved Earth Metal blades blades, I6.7 to 10.4 m width

- E-T 875 available in 4 models Operating Width: 4.26 to 7.92m
- Transport Width: 4.88. to 5.55m Number of Shanks: 7-13

TIGER-MATE 255 FIELD CULTIVATOR 17 models from 6.8 m to 16.3 m working width

Superb constant depth shank design

NUTRI-PLACER / NUTRI-TILLER

- NH₂ fertilizer applicators

SPEED-TILLER COMPACT DISC

Operating Width: 6.25 to 12.5m Transport Width: 2.9 to 4.8m





1 model 98 hp

Available with Cabin, 4WD

12x12 or 20x12 optional creeper

JX95 HIGH CLEARANCE

Wheels 340/85R38 or

optional 230/95R44

■ 616 mm ground clearan



SIMPLE AND RELIABLE

- Straddle, ROPS, 2WD/4WD
- Mechanical injection, Tier 1 / Tier 3 engine ■ 8x2 or optional 12x3 with creeper, partial synchromesh
- between 3rd and 4th speed gears Up to 2000kg lift capacity





WD1905



MAXXUM

5 models from 112 to 141 hp MAXIMUM VERSATILITY, MULTI-PURPOSE WORKHORSE

MAXXUM 110, 125, 140

- 5 models in 3 different levels of comfort: Value Line and X Line
- Open Operator Platform (110, 125) or Cab (110, 125, 140) Powered by mechanical 4 and 6
- cylinder FPT engines or 6 cylinder Common Rail (High models), Tier 3 24x24 HiLo or 16x16 Semi Power Shift transmission
- 80 I/min open center or 113 I/min
- CCLS hydraulic pump ■ Up to 7,868 kg max. lift capacity





JXT COMPACT

3 models from 36 to 49 hp

POWER AND ECONOMY

JX35T, JX40T, JX45T COMPACT ■ Straddle, ROPS, 2WD/4WD Mechanical injection, Tier 2 engine

8x2 or optional 8x8,

constant mesh transmission

HEAVY-OFFSET 790 DISK HARROW

12 models all-purpose or ploughing

■ 71 or 83 cm Earth Metal blades, solid or notched

Conventional or vertical tillage versions

8 models conventional True-Tandem 375 seedbed disc, 6.7 to 14.3 m working width, 8 models vertical tillage True-Tandem 335VT seedbed disc, for flattest floor and surface, ■ 7 models Min-Till True-Tandem 335 Barracuda disc harrow, aggressive toothed wave





ECOLO-TIGER DISK RIPPER

■ 3 types of sweeps, arranged in industry leading split-the-middle design

Nutri-Placer 930 with high speed low disturbance row unit Nutri-Tiller 955 with no-till compaction shuttering, residue cutting shank/knife combination

Speed-Tiller 475 available in 4 models





