



**MACHINE  
OF THE YEAR 2019**

**TIS**

**AUTO COMMAND™**



You're a professional farmer adding value to the things you grow. Productivity, comfort and ease of operation count. The New Holland T5 Auto Command™ has the features that will get your job done.

**SMOOTH POWER WITH CLASS LEADING FUEL ECONOMY:**

The T5 Auto Command™ range comes with the latest Stage V FPT Engines. Peak Power at 1800 RPM aligns perfectly with PTO and Transport operations. The neat package under the hood is compact and EGR Free.

**EFFICIENT AUTO COMMAND™ TRANSMISSION:**

Fully Automatic with seamless gear changes from 0 - 40 kph means you can achieve the speed you need with optimal fuel consumption. Adjustable acceleration settings to suit the job at hand, and fast direction changes with full Power shuttle. All controls at your fingertips.

**T5 AUTO COMMAND™.**  
**COMFORT, POWER, AND**  
**ADVANCED FEATURES IN**  
**AN AGILE PACKAGE**



# COMPACTNESS & FUNCTIONALITY WITH ADVANCE TECHNOLOGY.

The IntelliView IV touchscreen display allows you to manage and adjust tractor functions whilst also giving intuitive control over a range of guidance features such as Headland Turn Sequencing (HTS), ISOBUS III Control, and IntelliSteer® and IntelliTurn™.

## SPACIOUS HORIZON CAB.

Space and comfort in a fully suspended cabin. 4 post design provides excellent visibility with whisper quiet noise levels.

At night visibility remains optimal with up to 16 LED Cab mounted work lights giving 360° illumination. Climate controlled air conditioning to suit all seasons.



## MODELS

### T5.120 Auto Command™

### T5.140 Auto Command™

#### ENGINE - FPT

No. of Cylinders/Capacity/Valves/Emmissions management	4/4485/4/Stage V ECOBlue™ HI-eSCR 2 System	
Max Horsepower - ISO TR14396-ECE R120 (kW/hp)	88/120	103/140
Rated Horsepower @ rated speed 2200rpm -ISO TR14396- ECE R120 (kW/hp)	81/110	96/130
Max Torque - ISO TR14396 (Nm)	551@1300rpm	630@1300rpm
Diesel Tank capacity / AdBlue tank capacity (litres)		180/19
Alternator (amps)		200
Battery (Amp /Hr)		140
Reversible Engine fan		o

#### AUTO COMMAND™ Continuously Variable Transmission (CVT)

Min Speed / Max speed @1600rpm	0.02/40
--------------------------------	---------

#### STANDARD CLASS 1.5 HD Front Axle

Class 1.75 Front Axle with Steering Sensors	o
Terraglide™ front axle suspension	o
Terralock™ Auto Diff & Auto 4WD	s
Turning Radius for 4WD/ Terraglide™ suspended front axle (mm)	4615

#### 3 SPEED REAR PTO inc Ground Speed

Engine Speed at 540/540E/1000	1969/1546/1893
Ground Speed PTO	s
Front PTO (1000 rpm/ Max 115hp)	o

#### HYDRAULICS

MegaFlow™ Main Pump (lpm/Bar)	113/200
Steering and Services Pump (lpm/bar)	36.3/230
Rear Remote Valves- 2 Mechanical, 1 Elec Hyd	s
Rear Remote Valves- 2 Mechanical, 2 Elec Hyd	o
Mid Mount Valve inc 4 way Joystick- 2 Elec Hyd	o

#### 3 POINT LINKAGE

Electronic Draft Control (EDC)	s
Max Rear Linkage Lift Capacity at ball ends (kg)	5500
Max Front Linkage Lift Capacity at ball ends (kg)	2250

#### 4 PILLAR HORIZON™ CAB

High Visibility roof hatch	s	
Comfort Ride™ Cab Suspension	s	
Automatic climate control	s	
Deluxe Radio with Bluetooth & Hi Performance speakers	s	
Instructor Seat	o	
Blue Power Pack	n/a	o
12 LED lighting pack/16 LED lighting pack	s/o	

#### PLM (Precision Land Management)

ISOBUS Socket Class III + Speed Control	o
Headland Control System/Advanced Headland Control System	s/o
Autoguidance ready Steering. Level 1,2 or 3	o
Advanced Telematics	o

#### DIMENSIONS

Max Overall length inc weight carrier to rear linkage (mm)	4397
Min Width Narrow Guards/Standard Guards (mm)	1888/2288
Height from centre of rear axle to top of Cab (mm)	2100
Wheelbase (mm)	2490
Minimum Shipping Weight (kg)	5500
Gross Vehicle Weight max (kg)	8800

s = standard o = optional. Data shown is approximate and subject to change by manufacturer.



Visit [newholland.com/au](http://newholland.com/au)  
or scan the QR code

