

CRAWLER EXCAVATORS

CX210E-S



ENGINE

Model _____ FPT NEF6
 Type _____ Water-cooled, 4-cycle diesel, 6-cylinder in line, High pressure common rail system (electric control), Turbocharger with air cooled intercooler, SCRoF, EGR free.
 Number of cylinders / Displacement (l) _____ 6 / 6.7
 Emissions level _____ Stage V
 Bore and stroke (mm) _____ 104 x 132

Rated flywheel horse power

ISO 9249 (kW) _____ 120.4 at 1800 min⁻¹ (rpm)
 ISO 14396 (kW) _____ 124.0 at 1800 min⁻¹ (rpm)

Maximum torque

ISO 9249 (Nm) _____ 644 at 1600 min⁻¹ (rpm)
 ISO 14396 (Nm) _____ 657 at 1600 min⁻¹ (rpm)

HYDRAULIC SYSTEM

Main pumps _____ 2 variable displacement axial piston pumps with regulating system
 Max. oil flow (l/min) _____ 2 x 211 at 1800 min⁻¹

Working circuit pressure

Boom/Arm/Bucket (MPa) _____ 34.3 - 37.3 with auto power boost
 Swing circuit (MPa) _____ 29.4
 Travel circuit (MPa) _____ 34.3
 Pilot pump (l/min) _____ 18
 Working circuit pressure (MPa) _____ 3.9

Boom cylinders

Bore (mm) _____ 120
 Stroke (mm) _____ 1255

Arm cylinder

Bore (mm) _____ 140
 Stroke (mm) _____ 1460

Bucket cylinder

Bore (mm) _____ 120
 Stroke (mm) _____ 1010

SWING

Swing motor _____ Fixed displacement axial piston motor
 Maximum swing speed (min⁻¹) _____ 11.5
 Swing torque (kNm) _____ 64

FILTERS

Suction filter (µm) _____ 105
 Return filter (µm) _____ 6
 Pilot line filter (µm) _____ 8

ELECTRICAL SYSTEM

Voltage (V) _____ 24
 Alternator (Amp) _____ 90
 Starter (V - kW) _____ 24 - 4.0
 Battery _____ 2 x 12 V 110 Ah - 880 ACC

UNDERCARRIAGE

Travel motor _____ Variable displacement axial piston motor
 High travel speed (Automatic travel speed shifting) (km/h) _____ 5.6
 Low travel speed (km/h) _____ 3.4
 Drawbar pull (kN) _____ 181
 Number of carrier rollers (each side) _____ 2
 Number of track rollers (each side) _____ 8
 Number of shoes (each side) _____ 49
 Type of shoes _____ Triple grouser shoes
 Gradeability _____ 70% (35°)

NOISE (PRELIMINARY)


External guaranteed sound level (EU Directive 2000/14/EC) (dB(A)) _____ LwA 100
 Operator cab sound pressure level (ISO 6396) (dB(A)) _____ LpA 68

CIRCUIT AND COMPONENT CAPACITIES

Fuel tank (l) _____ 410
 Hydraulic system (l) _____ 280
 Hydraulic tank (l) _____ 162
 AdBlue tank (l) _____ 84


PERFORMANCE DATA		Arm 2.94 m
Boom length	mm	5700
Bucket radius	mm	1450
Bucket wrist action	°	177
A Maximum reach at GRP	mm	9730
B Maximum reach	mm	9900
C Max. digging depth	mm	6640
D Max. digging height	mm	9610
E Max. dumping height	mm	6810
F Min. swing radius	mm	3660

DIGGING FORCE (ISO 6015)		Arm 2.94 m
Arm digging force	kN	103
with auto power boost	kN	112
Bucket digging force	kN	142
with auto power boost	kN	154



SPECIFICATIONS

CX210E-S LC MONO



GENERAL DIMENSIONS		Arm 2.94 m
A	Overall length (without attachment)	mm 5050
A1	Overall length (with attachment)	mm 9470
B	Overall height (to top of boom)	mm 2980
C	Cab height	mm 3070
D	Overall height (to top of guardrail)	mm 3155
E	Upper structure overall width	mm 2760
F	Swing (rear end radius)	mm 2830
G	Clearance height under upper structure	mm 1040
G	Minimum ground clearance	mm 440
I	Wheel base (center to center of wheels)	mm 3660
J	Track gauge	mm 2390
K	Undercarriage overall width (with 600 mm HD shoes)	mm 2990
L	Crawler overall length	mm 4470
M	Crawler tracks height	mm 920

WEIGHT AND GROUND PRESSURE

With 2.94 m arm, 1.08 m³ HD bucket, operator, lubricant, coolant, full fuel tank, FOPS protection level 2 and standard counterweight.

	WEIGHT	GROUND PRESSURE
600 mm HD grouser shoes	22240 kg	0.046 MPa
700 mm grouser shoes	22540 kg	0.040 MPa

STD Counterweight: 3800 kg
HEAVY Counterweight: 3800 kg + 500 kg

LIFTING CAPACITY

CX210E-S LC MONO

REACH											
	2.0 m		4.0 m		6.0 m		8.0 m		At max reach		
	Front	Side	Front	Side	Front	Side	Front	Side	Front	Side	m
LC UNDERCARRIAGE - Standard arm 2.94 m, 600 mm shoes, max reach 8.45 m											
8.0 m									4060*	4060*	5.72
6.0 m					4780*	4780*			3595*	3595*	7.33
4.0 m			7190*	7190*	5540*	5015	4535*	3115	3540*	3000	8.16
2.0 m			10360*	8350	6690*	4630	4725	2990	3740*	2735	8.45
0 m			11925*	7780	7085	4340	4610	2885	4265*	2760	8.25
-2.0 m	9230*	9230*	11725*	7730	6990	4255			5030	3140	7.53
-4.0 m	16490*	16490*	9900*	7985	6290*	4430			6125*	4355	6.09
LC UNDERCARRIAGE - HEAVY COUNTERWEIGHT - Standard arm 2.94 m, 600 mm shoes, max reach 8.45 m											
8.0 m									4060*	4060*	5.72
6.0 m					4780*	4780*			3595*	3595*	7.33
4.0 m			7190*	7190*	5540*	5315	4535*	3330	3540*	3210	8.16
2.0 m			10360*	8870	6690*	4930	4990	3200	3740*	2935	8.45
0 m			11925*	8300	7475	4640	4870	3095	4265*	2965	8.25
-2.0 m	9230*	9230*	11725*	8250	7380	4555			5315	3365	7.53
-4.0 m	16490*	16490*	9900*	8505	6290*	4730			6125*	4650	6.09

* The above loads (kg) are compliant to the ISO standards and refer to the excavator equipped without bucket. The indicated loads are no more than 87% of hydraulic system lift capacity or 75% of static tipping load. Values marked with an asterisk (*) are limited by the hydraulic lifting capacity.

HAMMER


CX210E-S LC MONO

DIRECT FIT

Model	Install weight kg	Reference machine setting		Arm 2.94 m
		Flow l/min	Relief pressure MPa	
CB BREAKER				
CB240S	1150	115	19-21	□
CB290S	1500	145	21-22	□

□ Applicable
— Not applicable

□ Applicable with condition
(only light duty works as residential construction or utilities maintenance)



BUCKETS

CX210E-S LC MONO

LC DIRECT FIT



Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
HEAVY DUTY BUCKETS			
0.45	600	560	○
0.60	750	640	○
0.76	900	730	○
0.85	1000	760	○
0.92	1050	800	○
0.96	1100	830	○
1.08	1200	880	●
1.24	1350	970	▲
1.40	1500	1040	■

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
ROCK BUCKETS			
0.44	600	710	○
0.59	750	800	○
0.75	900	880	○
0.85	1000	940	○
0.91	1050	980	○
0.96	1100	1010	●
1.07	1200	1060	▲
1.23	1350	1150	■

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
DITCH CLEANING BUCKETS			
0.86	1830	650	○
0.94	2130	710	○

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
GRADING BUCKETS			
0.97	1800	680	○
1.17	2100	740	●
1.35	2400	830	▲

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
90° TILT DITCH CLEANING BUCKETS**			
0.68	1800	770	○
0.76	2000	810	○
0.83	2200	880	○
0.91	2400	920	●
0.95	2500	950	●

LC QUICK COUPLED



Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
HEAVY DUTY BUCKETS			
0.45	600	560	○
0.60	750	640	○
0.76	900	730	○
0.85	1000	760	○
0.92	1050	800	●
0.96	1100	830	●
1.08	1200	880	▲
1.24	1350	970	■
1.40	1500	1040	—

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
ROCK BUCKETS			
0.44	600	710	○
0.59	750	800	○
0.75	900	880	○
0.85	1000	940	●
0.91	1050	980	●
0.96	1100	1010	▲
1.07	1200	1060	■
1.23	1350	1150	—

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
DITCH CLEANING BUCKETS			
0.86	1830	650	○
0.94	2130	710	●

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
GRADING BUCKETS			
0.97	1800	680	●
1.17	2100	740	▲
1.35	2400	830	■

- Rated material density up to 2 ton/m³
- Rated material density up to 1.6 ton/m³
- ▲ Rated material density up to 1.4 ton/m³
- Rated material density up to 1.2 ton/m³

- Not applicable
- * with bolt-on edge
- **Tilt angle 45° L/R Connect to Low-Flow Auxiliary Hydraulic Circuit

BUCKETS

CX210E-S LC - HEAVY COUNTERWEIGHT



LC DIRECT FIT

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
HEAVY DUTY BUCKETS			
0.45	600	560	○
0.60	750	640	○
0.76	900	730	○
0.85	1000	760	○
0.92	1050	800	○
0.96	1100	830	○
1.08	1200	880	○
1.24	1350	970	●
1.40	1500	1040	▲

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
ROCK BUCKETS			
0.44	600	710	○
0.59	750	800	○
0.75	900	880	○
0.85	1000	940	○
0.91	1050	980	○
0.96	1100	1010	○
1.07	1200	1060	●
1.23	1350	1150	▲

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
DITCH CLEANING BUCKETS			
0.86	1830	650	○
0.94	2130	710	○

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
GRADING BUCKETS			
0.97	1800	680	○
1.17	2100	740	○
1.35	2400	830	●

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
90° TILT DITCH CLEANING BUCKETS**			
0.68	1800	770	○
0.76	2000	810	○
0.83	2200	880	○
0.91	2400	920	○
0.95	2500	950	●



LC QUICK COUPLED

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
HEAVY DUTY BUCKETS			
0.45	600	560	○
0.60	750	640	○
0.76	900	730	○
0.85	1000	760	○
0.92	1050	800	○
0.96	1100	830	○
1.08	1200	880	●
1.24	1350	970	▲
1.40	1500	1040	■

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight kg	Arm 2.94 m
ROCK BUCKETS			
0.44	600	710	○
0.59	750	800	○
0.75	900	880	○
0.85	1000	940	○
0.91	1050	980	●
0.96	1100	1010	●
1.07	1200	1060	▲
1.23	1350	1150	■

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
DITCH CLEANING BUCKETS			
0.86	1830	650	○
0.94	2130	710	○

Capacity m ³ (ISO7451 HEAPED)	Width mm	Weight* kg	Arm 2.94 m
GRADING BUCKETS			
0.97	1800	680	○
1.17	2100	740	●
1.35	2400	830	▲

- Rated material density up to 2 ton/m³
- Rated material density up to 1.6 ton/m³
- ▲ Rated material density up to 1.4 ton/m³
- Rated material density up to 1.2 ton/m³

— Not applicable
* with bolt-on edge

**Tilt angle 45° L/R Connect to Low-Flow Auxiliary Hydraulic Circuit

BUILDING A STRONG CASE.

Since 1842, at CASE Construction Equipment we have lived by an unwavering commitment to build practical, intuitive solutions that deliver both efficiency and productivity.

We continually strive to make it easier for our customers to implement emerging technologies and new compliance mandates.

Today, our global scale combined with our local expertise enables us to keep customers' real-world challenges at the center of our product development.

The vast CASE dealers' network is always ready to support and protect your investment and exceed your expectations, while also providing you with the ultimate ownership experience.

Our goal is to build both stronger machines-and stronger communities. At the end of the day, we do what's right for our customers and our communities so that they can count on CASE.

CNH Industrial
Deutschland GmbH
Case Baumaschinen
Benzstr. 1-3 - D-74076 Heilbronn
DEUTSCHLAND

CNH Industrial
Maquinaria Spain, S.A.
Avenida Aragón 402
28022 Madrid - ESPAÑA

CNH Industrial France, S.A.
16-18 Rue des Rochettes
91150 Morigny-Champigny
FRANCE

CNH Industrial Italia Spa
Lungo Stura Lazio 19
10156, Torino
ITALIA

CASE Construction Equipment
Cranes Farm Rd
Basildon - SS14 3AD
UNITED KINGDOM

NOTE: Standard and optional fittings can vary according to the demands and specific regulations of each country. The illustrations may include optional rather than standard fittings - consult your Case dealer. Furthermore, CNH Industrial reserves the right to modify machine specifications without incurring any obligation relating to such changes.

Conforms to directive 2006/42/EC

CASECE.COM
00800-2273-7373

The call is free from a land line.
Check in advance with your Mobile Operator if you will be charged. Toll free number not available from all calling areas.