PATRIOT[®]

285 – 390 hp

CASEI



PATRIOT 50 SERIES SPRAYERS

3 models | 285–390 hp | 3,028 I to 6,057 I

EXCEPTIONAL PERFORMANCE, INTEGRATED TECHNOLOGY, AGRONOMIC DESIGN

For decades, growers and custom applicators have trusted the Patriot[®] sprayer to take on tight application windows — but on today's operations, it takes more than timely, accurate spraying to drive profitability. You need complete vehicle control and a cab with built-in luxury — because comfortable operators are productive operators. And, you not only need connectivity and remote management capabilities to make better, data-driven decisions but also the ability to manage and coordinate your fleet from anywhere. Patriot 50 series sprayers deliver all that while building on the Agronomic Design[™] principles Case IH sprayers are known for.

Images are for display purposes only. Consult your local Case IH dealer to confirm actual machine specification

PATRIOT 50 SERIES SPRAYERS

INEREX

Leading the Industry
Machine Configuration
Connectivity and Support
AFS Connect and Slingshot
Operator Environment 12–13
Drivetrain and Suspension 14–15
Quality of Application 16 – 17
Ultimate Spray Technology 18–19

100

Application Options	20-21
Lighting Package	22-23
Advanced Tyre Technology	24-25
Patriot Family	26-27
Service Center and Storage	28-29
Confidence and Control	30
Product Specifications	31



TAKE CONTROL OVER YOUR PRODUCT APPLICATION

In our industry, there's a lot that's out of our control — input costs, markets, Mother Nature. The Patriot 50 series sprayer is designed to help you expertly manage what you can control to maximise yield potential: crop protection and fertility applications. Plus, with a wide range of configurations and options, there's a model that fits your needs.



Consult your local Case IH dealer for configurations and options.



COMFORT & PERFORMANCE

- With a quiet, comfortable interior that boasts an abundance of glass for maximum, unrestricted visibility, a premium cab is designed to increase operator performance.
- Experience superior ride quality, stability and control with a **4-bar linkage chassis suspension system**.
- The MultiControl Armrest layout provides exceptional ergonomics, with a comfortable operator seat that swivels 30 degrees to the right.

INTEGRATED TECHNOLOGY

- Connected solutions integrated into every Patriot 50 series sprayer provide endless opportunities for your operation.
- A suite of technology solutions which are capable of performing wireless file transfers, sharing guidance lines, creating prescription maps, fleet management, data sharing and product control.
- AIM Command FLEX[™] II advanced spray technology ensures consistent chemical application rate, pressure and droplet size, with individual nozzle on/off control for increased accuracy and efficiency.

AGRONOMIC DESIGN

- The proven **cab-forward**, **rear-engine design** helps you achieve timely application with optimised weight distribution, getting you into fields sooner with less compaction.
- **Strong, durable booms are built with robust material,** while the boom suspension design helps provide a stable platform for product application.
- Take accurate and effective coverage to the next level with the integrated AutoBoom[®] XRT Automatic Boom Height control that detects and accommodates changes in terrain.
- A new center section design minimises boom yaw in challenging conditions — even with longer boom options.

NEW LOOK, SAME PATRIOT DNA

No matter how trusted and reliable, it's tough to teach an old sprayer new tricks. That's why we redesigned the Patriot 50 series sprayer from the ground up — while keeping the Agronomic Design features that mattered to you most. For decades, the distinctive cab-forward, rear-engine design and strong, durable boom have been critical to helping operators achieve accurate, timely spraying. And now, the Patriot sprayer combines those key elements with the most advanced technology to take high-efficiency spraying to the next level.



ULTIMATE CONNECTIVITY

A suite of solutions and options to ensure machines are set up for the tasks at hand, tracking machines, jobs and field data.



BOLD, NEW STYLING

With redesigned front and rear hoods, the look of the Patriot sprayer embodies all of what you expect from Case IH application equipment and technology: power, innovation and efficiency.

C AWARD-WINNING ARMREST

Operators of current model Steiger[®] and Magnum[™] series tractors will feel at home with the exceptional ergonomics of the Patriot 50 series sprayer MultiControl Armrest and MultiFunction Handle all mounted to the seat for easier operation as you move and swivel.



CASEL

ADVANCED SPRAY TECHNOLOGY

D

CASEN

LAAAT

High-quality and accurate application is made possible by AIM Command FLEX II advanced spray technology, which offers severe duty poppets, individual nozzle on/off control and is capable of higher flow rates.

SUPERIOR RIDE

E

A 4-bar linkage chassis suspension system gives you better ride quality and keeps you in control through smoother suspension and higher wheel travel to help boost productivity.

ONE PRODUCTIVE DUO

Connected solutions and options provide endless opportunities for your operation — whether you're running a single Patriot 50 series sprayer or a fleet of them. With the power of **AFS Connect™** and **Raven Slingshot®**, you have the unmatched connectivity, guidance, data and monitoring solutions you need to ensure your machines are ready for the tasks at hand.

COMPLETE VISIBILITY & CONTROL

• With two customisable displays — the AFS Pro 1200 and the Viper 4+ — operators always have top-of-the-line vehicle and product control and the real estate to see what they want, when they want.

AFS PRO 1200 | MACHINE INTERFACE

 Powered by the AFS Vision Pro operating system, the AFS Pro 1200 provides precise control over every aspect of the chassis from cab climate settings to exterior lighting controls, to Bluetooth[®] and radio settings and even initiating the reversing engine fan operation.

VIPER 4+ | PRECISION FARMING

• With the Viper 4+ display, take precise application to the next level with product control and autoguidance solutions.

FULL REMOTE VISIBILITY

- **Remote Display Viewing.** With the operator's permission, Case IH dealers and distributors as well as farm and operation managers can remotely see exactly what is on screen in the cab to assist with machine setup and optimisation.
- **Remote Service Support.** There's no time for downtime. Now, you can work with your local Case IH dealer or distributor to remotely diagnose maintenance and service issues and to identify the parts you need.
- **Remote Software Updates.** Your local Case IH dealer or distributor can remotely push updates to your operating firmware wirelessly to take advantage of new features, functionality and enhancements.

VEHICLE HISTORY & MONITORING

- View and track every connected vehicle's path to and from the field to ensure uptime and productivity.
- Monitor sprayer progress across the field to improve tendering logistics.
- Vehicle tracking history and machine data can be referenced to identify equipment trends and enhance long-term productivity and efficiency.

GEOFENCING & CURFEWS

- Keep an eye on your fleet and receive notifications when equipment travels in or out of set boundaries.
- Set geofence boundaries to alert the tender truck operator when a sprayer is leaving the field so they're ready to refill.
- Add a machine curfew, so you're quickly alerted if a machine is operating after hours.





NEXT-LEVEL PRECISION

The Patriot 50 series sprayer utilises the Vector Pro receiver for ultimate in field performance.

AFS VECTOR PRO RECEIVER

- Equipped with SC1 guidance, the AFS Vector Pro receiver provides reliable and consistent terrain-compensated position and helps operators quickly acquire guidance lines.
- Streamlined guidance correction options, ranging from base (AFS 1) to medium (AFS 2 and AFS 3) to high (RTK and NTRIP) accuracy levels.
- Compatible with the AutoTurn automated headland turning option.



YOU'RE IN CONTROL

With AFS Connect and Slingshot, included with SC1 guidance options, you can keep an eye on your fleet and operation — anytime, anywhere.

AFS CONNECT

- Every Patriot 50 series sprayer comes with an AFS Connect-compatible modem and a 5-year subscription from the factory.
- With an AFS Connect subscription, these features give you full visibility to your operation and maximise your uptime:

- Data Visualisation: View and store your application maps for full season-to-season record keeping and visualisation.
- **Prescription Tool:** Create application prescriptions, then export and easily transfer to your Viper 4+.
- Equipment Mode: Toggle on and off machine location information to see your fleet when you need to.
- Vehicle Location History: Track machine location, parameters, and progress during jobs to better plan tasks like tendering logistics.
- Remote Display Viewing: View the AFS Pro 1200 from your desktop to coach operators on machine setup and operation.
- Remote Service: Connect with your dealer or distributor to update machine controllers and view detailed machine information.

SLINGSHOT

Ensure your machines are set up for the tasks at hand. Plus, with a Slingshot mobile solution, easily view and monitor your vehicles from anywhere.

With a 5 year slingshot gold subscription, included with SC1 guidance, these capabilities can maximise your operation's efficiency:

Job Generator: Set up jobs in the office and dispatch to the Viper 4+ in sprayers out in the field.

Job Sync: Share live coverage maps and guidance lines between two or more sprayers working in the same field. Fleet View: Fleet or operations managers can see sprayer details in real time.

Slingshot Link: Enables over-the-air updates to the Viper 4+, and other hardware.

File Transfer: Allows for the transfer of data from sprayer to office and office to sprayer.

Remote Support: Remote, live viewing of the display in the sprayer to aid operators with setup or troubleshooting.





- Luxury leather, heated/ventilated seat with 30-degree swivel to the right
- B Carpet floor mat
- C Leather seat
- More than 7.5 square meters of glass for unrestricted visibility
- (E) Elevated foot rest
- F Leather-wrapped steering wheel
- Telescoping steering wheel with memory lock

- (H) Digital instrument cluster display
- I AFS Pro 1200 display
- Viper 4+ display
- K Leather MultiControl Armrest
- L Audio system
- M Power ports





YOU'VE NEVER EXPERIENCED A CAB **SO COMFORTABLE**

Case IH engineers used years of research and customer input to design an operator environment so comfortable and quiet that operators won't mind those long days in the field. With a cab that perfectly blends simplicity, control and luxury, the Patriot sprayer puts productivity first.

A Speed presets B Boom tilt up/down C Autosteer engage Center section raise/lower E Speed scroll wheel F Forward-reverse propel

quick shuttle

- G Traction control H Throttle controls
- K
- Customisable hot keys Tread adjust Auto-fold/unfold



controls at your fingertips.

CONTROL MADE SIMPLE

F.

a series

XUA

The same award-winning armrest design from current model Steiger and Magnum series tractors provides exceptional ergonomics and ease of use.

MULTICONTROL ARMREST

CASEII

1.2.1 -----

IX Marriel attack attack

BUILTING BUILTING ET

Administrator

Attached to the operator seat, this armrest puts all controls and customisable hot buttons within reach.

EFFICIENT POWER, UNMATCHED PERFORMANCE

At the heart of every Patriot 50 series sprayer is an engine designed to deliver the power you need to work long days, economically cover thousands of hectares and handle tough terrain. Case IH FPT engines offer extended maintenance intervals and enhanced fuel economy — helping you minimise operating costs.

BOOST TRAVEL SPEEDS

- We engineered the hydrostatic drive system to enable you to reach a wide range of speeds — and do so without the need to shift between ranges
- Increased transport speeds of up to 59.5 kph (Patriot 4350 and 4450 sprayers) help you get from field to field faster so you can cover more acres in a day.
- A spring-centered propulsion handle and speed scroll wheel help you reach your desired speed with ease.
- Integrated individual-wheel traction control enhances performance by automatically sensing wheel slip and regulating oil flow at each wheel motor to power through challenging conditions.

ROBUST DRIVETRAIN

- Drivetrain components are engineered to work as hard as you do.
- Infinitely variable hydrostatic pump and drive motors allow you to set your desired speed without the need to change ranges.
- · Planetary hubs offer internal parking and service brakes.
- Forward/reverse quick shuttle makes changing direction of travel an easy process with the ability to set predetermined speed settings — all without having to move the MultiFunction Handle.
- Two speed preset selections are customisable to meet your specific needs.

REVERSING ENGINE FAN

 For operators in conditions with high amounts of field debris, a reversing engine fan clears the grill screen and cooling cores — so you're always running under optimal conditions.

CRUISE THROUGH LONG DAYS WITH AN ULTRA-SMOOTH RIDE

We know comfortable operators are more productive operators. The Patriot 50 series sprayer delivers superior ride quality thanks to a 4-bar linkage chassis suspension system with 203 mm of total suspension travel. Best of all, it's designed for increased stability to keep you in control no matter what terrain you're working in.

SUPERIOR RIDE QUALITY

- Innovative **4-bar linkage chassis suspension system** addresses both vertical and horizontal field loads with 203 mm of total suspension travel.
- Softer, **air ride suspension** paired with higher wheel travel provides unmatched shock absorption and load dampening.
- Tuned for Patriot 50 series sprayers, shock absorbers provide increased operator control during aggressive acceleration or braking and enhance ride quality and comfort during field operation.
- **Rebound and jounce bumpers** help limit component travel and dampen the casting loads, resulting in a softer ride over challenging terrain.
- Accessible grease banks make it easier to maintain your suspension system and keep it operating at peak performance.
- Effective **suspension system shields** help gently move plants away from suspension components to minimise crop contact.





DURABLE BOOMS MEET POWERFUL TECH

Every boom width on Patriot 50 series sprayers incorporates the same strong, advanced boom suspension design that operators have come to rely on. The parallel-link design packs superior strength without excessive weight and seamlessly incorporates boom technology options that take application accuracy and efficiency to the next level.

STRONG & STABLE

 Built with robust materials, Patriot 50 series sprayer booms deliver a stable platform for product application — even in the toughest conditions — through proven boom suspension design. And when you're getting ready for transport, booms are automatically locked when placed in the cradle, keeping them secure.

AUTOFOLD PLUS

• Every boom option is equipped with an automated fold/ unfold feature for maximum ease of use — just push and hold the AutoFold Plus switch on the MultiControl Armrest and the booms smoothly fold/unfold so you can get moving faster.

ACCUBOOM

- Operated through the Viper 4+ display, AccuBoom Automatic Boom Section control automatically turns off boom sections when the sprayer enters an area that has already been sprayed and then turns the sections back on when leaving the applied area.
- Customise overlap and section control to meet your desired field results and reduce over application to save on inputs.



AUTOBOOM XRT

- The integrated AutoBoom[®] XRT Automatic Boom Height control detects and accommodates changes in terrain for more accurate and effective coverage across every cm of ground.
- Coupled with the innovative Patriot boom suspension design, AutoBoom XRT delivers solid boom control and stability.
- Radar sensors can be configured to detect the location of the ground or crop canopy to maintain a level spray platform and maximise boom life.



Command

ADVANCED SPRAY TECHNOLOGY

With AIM Command FLEX II advanced spray technology, you get the best possible chance at maintaining your ideal chemical application rate, pressure and accuracy. This innovative technology is capable of higher flow rates and incorporates individual nozzle on/off control to ensure efficient, precise application — regardless of speed or terrain.

OPTIMISE APPLICATION

- AIM Command FLEX II technology optimises application rates and droplet sizes for consistent application, regardless of speed and ground conditions.
- With **six modes of operation**, this advanced spray technology delivers flexible and accurate application even in turns, rough terrain and irregular-shaped fields.
- Standard individual nozzle on/off control minimises input costs and improves accuracy by reducing skips and overlaps.
- Enhanced nozzle control valves are higher-flow-capable, so you can spray at faster speeds or apply more product as needed, while severe-duty poppets help extend operating life.

HOW IT WORKS

- Pulse width modulation (PWM) spray technology ensures a constant application rate and spray pressure, even when sprayer speed changes. Think of it as a way to change nozzle tips without leaving the cab.
- Once you select a standard tip based on application rate, chemical droplet size and travel speed, AIM Command FLEX II technology automatically and precisely controls the flow to meet targeted application rates.
- Operators select their desired frequency, working between 10 and 20 pulses per second, nozzle control valves vary the duty cycle to maintain the correct application rate as sprayer speed changes.

TURN COMPENSATION

- AIM Command FLEX II technology effectively compensates for different speeds across the boom to ensure correct application rates during turns.
- Each nozzle adjusts its duty cycle to match the targeted application rate based on speed, nozzle position on the boom and turn radius.

PRECISE PRODUCT FLOW

- AIM Command FLEX II technology provides individual nozzle on/off control, delivering the ultimate in spray accuracy and precision.
- The ability to control spraying at the individual-nozzle level helps **reduce over application** that adds costs and results in potential crop damage.
- To accommodate sprayer wheel tracks, fence rows or other field conditions, you can preset spray rates up to 30% higher than your target rate on up to eight nozzles.

IMPROVED DRIFT CONTROL

- For on-demand drift control, AIM Command FLEX II technology allows you to toggle between two preset spray pressures that can be reset up or down at any time.
- Input a lower pressure setting to selectively avoid off-target application in sensitive areas or to respond to wind gusts. When normal conditions return, toggle back to the higher pressure setting on the go.
- You also have the option of inputting a higher pressure setting for greater canopy penetration.



BOOST YOUR APPLICATION POTENTIAL

Whether you're applying crop protection or fertility products, you can now drive productivity gains with maximum product flow capabilities — and maintain exceptional accuracy at any rate. Plus, a direct injection option allows operators to apply product to the entire field or selectively treat only certain portions based on pest pressure, helping you save on input costs and minimise waste.

WIDE RANGE OF FLOW CAPABILITIES

- With AIM Command FLEX II technology, nozzle control valves are capable of higher flow rates and increased operating pressure — so you can spray more product at faster speeds and maintain accuracy.
- Product plumbing is sized to match your application rate and speed requirements.

MATCH YOUR APPLICATION NEEDS

- A stainless steel pump housing helps enhance pump life when spraying corrosive and abrasive products.
- Add on nozzle body options can be dealer installed offering enhanced flexibility and versatility to your spraying operation:
 - For increased product flow: Wilger Combo-Rate II nozzle bodies provide a larger inlet diameter.
 - For two-body spraying: Add another single-outlet end body when higher flow applications may be desired.
 - For even greater flexibility: Choose from two 5-way turret body options one version includes a radial lock design for all outlets, while another version provides three outlets with a square lug design and two with the radial lock design.



HAVE GREATER CONTROL WITH DIRECT INJECTION

- Optional direct injection simplifies cleanout, as only the injection tanks and boom
 plumbing are used to carry application products no tank mixing required. That
 means quicker product changeover and decreased risk of misapplication when
 changing products.
- Choose from low- and high-flow pump options to match your needs.
 Save on input costs by varying chemical application on the fly ideal for when you need to spot-spray areas with weeds.

CONVENIENT RINSE PROCESS

- Patriot 50 series sprayers are designed for **easy, efficient cleaning** to help maintain application accuracy and minimise cross-contamination of products.
- **Boom flush valves** allow you to rinse out each boom tube, without having to go through spray tips and nozzle bodies.
- **Optional automated rinse system** allows for tank-filling, tank-rinsing or boom-rinsing and can be controlled at the service center or from the cab with your Pro 1200 display.

LIGHT UP THE NIGHT

When you need to finish the job after hours, enhanced LED light packages are brighter for better night time visibility and use less power. Every Patriot 50 series sprayer includes front hood-, cab-, and tank-mounted lighting — and a center section beacon light — to help ensure you can **operate safely while covering acres at night and during transport.**

CASE

DELUXE LIGHTING PACKAGE

CASED

For operators who frequently spray at night, **additional caband boom-mounted lights** provide maximum visibility and help you see all sprayer components and the terrain around you.

> SPRAY PATTERN LIGHTS Blue lens spray pattern lights, provide exceptional visibility of your application and nozzles.



KEEP ON ROLLING

With a range of tyre options and axle adjust capabilities, it's never been easier to match your needs and keep working through the toughest conditions. Plus, advanced tyre technology helps reduce compaction to enhance yield potential.

TYRE OPTIONS

- Tyre options with VF or LSW technology offer the advantage of lower inflation pressure to carry the sprayer's weight – which reduces compaction.
- Match your tyres to your row spacing, field conditions and terrain with a range of options and sizes.

FENDERS & MUD FLAPS

- Durable, factory-installed fender narrow or wide are designed to match your tyre selections.
- When you're operating in challenging, wet conditions, **mud flaps** can help keep your sprayer clear of debris a standard feature with wide and narrow fenders.

AXLE ADJUSTMENT OPTIONS

- Every Patriot 50 series sprayer provides the ability to hydraulically adjust track width to match your field conditions, terrain and row spacing.
- With the **automated axle adjust option**, just set your desired track width on the AFS Pro 1200 display and integrated sensors continually monitor the axle position to match.
- Further minimise compaction by setting front and rear axles at different widths, creating four sets of tracks.



MEET THE PATRIOT 50 SERIES FAMILY

PATRIOT 4350 SPRAYER

- 4,542 I tank capacity
- Case IH FPT engine: 335 base hp/374 peak hp
- Speed range 0-59.5 kph



PATRIOT 4450 SPRAYER

• 6,057 I tank capacity

12 00

- Case IH FPT engine: 390 base hp/415 peak hp
- Speed range 0-59.5 kph

PATRIOT 3250 SPRAYER

- 3,028 or 3,785 I tank capacity
- Case IH FPT engine: 285 base hp/309 peak hp

S. S. Stringer String of

• Speed range 0-51.5 kph

C /121

1. 建电空中间

TENDERING MADE EASY

CASEII

Maximise time in the field and get tendering or maintenance out of the way quickly and efficiently. Everything is within reach with a one-stop service center, exclusive tip wash station, ground-level connections and an open architecture design.

ONE-STOP SERVICE CENTER

- With a **midship-mounted service center**, you can perform all primary tendering functions from one central location.
- Choose from **manual rinse or an automated rinse option** with a user-friendly display interface at the service center.
- A convenient remote reload station allows operators to activate the on-board product pump for suction filling and speed up the engine as needed, while a suction quick-fill option can help you speed up the process.
- Consult your local Case IH dealer for configurations and options.



EASY-FILL OPTIONS

- The **optional fill flowmeter**, which can be positioned at either the service center or adjustable height front-fill location, monitors the volume of product added to the tank and automatically updates the tank level indicator on your Viper 4+ display.
- With the adjustable front fill, an **air blowout feature** makes cleaning the fill hose a breeze, blowing remaining product into the product tank.

CONVENIENT WASH STATION

• Mounted in the middle of the center section, an **exclusive tip wash station** provides an easy, accessible way for operators to clean off spray tips with both an air nozzle and water outlet.

MAXIMUM STORAGE

- An **exterior storage box** with two compartments comes standard, so you can store as many tools, PPE or maintenance items as you need.
- A RHS storage box is also fitted for additional storage.
 (NB: removed when direct injection options are added)
- An additional **in-cab storage compartment** is provided under the instructional seat, so you can pack up what you need and keep it out of the way while you're working.

SPRAY WITH CONFIDENCE

When time is of the essence, details matter. It's the smallest design elements, productivity-enhancing features, reliable technology and support networks that add up to deliver a high-efficiency operation. Agronomic Design is embedded in our DNA so you can apply the right amount of product at the right time — and every Patriot 50 series sprayer is backed by the best dealer and distributor networks in the business to keep you up and running.

5 WAYS THE PATRIOT 50 SERIES SPRAYER PUTS YOU IN CONTROL

- 1. Get in fields faster: The cab-forward, rear-engine design optimises weight distribution with less compaction, while faster speeds and efficient tendering mean more time in the field and less time on the sidelines.
- 2. Minimise variability: PWM spray technology automatically maintains droplet size and keeps application rates constant — reducing overapplication or underapplication and potential crop damage.
- 3. Manage inputs: AIM Command FLEX II advanced spray technology and individual nozzle on/off control reduces skips, overlaps and accommodates for turns.

- Maintain accuracy at your speed: Drive according to ground conditions without sacrificing accurate coverage thanks to AIM Command FLEX II technology.
- 5. Maximise uptime: Spray with confidence and achieve optimal return on your investment with exceptional support from the Case IH dealer and distributor network.

MODEL	PATRIOT 3250	PATRIOT 4350	PATRIOT 4450		
CAB					
Cab Interior Space		3.7 m ³			
Cab Glass Area		7.5 m ²			
Cab Trim		Luxury			
Operator Seat		Active seat with adjustable 30 degree swivel to the right			
Derator Seat Adjustments	Lumbar support, firmness and auto weight adjustments, fore/aft and lateral isolators, back cushion tilt, swivel, fore/aft position, and height				
IVAC System					
Cab Pressurisation	Cab pressure m	ionitored by HVAC system through the AFS Pro 1200, alerts displayed if cab pressure	falls below 20 Pa		
ENGINE					
Engine/Cylinders/Displacement	Case IH FPT Tier 3/6 Cyl/ 6.7L	Case IH FPT Tier	2/ 6 Cyl / 8.7L		
Engine hp	285 rated hp / 309 peak hp	335 rated hp / 374 peak hp	390 rated hp / 415 peak hp		
Peak Torque	1159 Nm	1550 Nm	1 706 Nm		
Iternator	240 amp standard / 330 amp supplied with Direct Injection kits				
uel Tank					
CHASSIS					
Crop Clearance		1346 mm			
Nheelbase	3.8 m	4.1 r	n		
Furning Radius	6.8 m	7.6 m	7.3 m		
hassis Suspension		4-wheel independent, 4-bar linkage design, air ride with tuned shock absorbe	r		
otal Suspension Travel	203 mm				
Wheel Track Adjustment (Standard/Optional)		7—4 064 mm hydraulically adjusted from the cab with manual stops at 2.5 cm incree n the cab; automatically adjusts to desired width entered into AFS Pro 1200 display.			
DRIVETRAIN					
ype		Hydrostatic			
I-Wheel Drive	Full-time with traction control feature				
Shifting/Number of Ranges		Infinitely variable with two programmable speed pre-sets			
		0-59.5			
Speed Range(s)	0—51.5 kph	0-09.0	kph		
	0—51.5 kph	0-33.3	kph		
YRES	0–51.5 kph VF380/90R46, LSW480/70R46	VF380/90R46, LSW480/70R46	kph VF380/105R50, VF480/80R50		
YRES ow Crop Tyre Selections	VF380/90R46, LSW480/70R46				
YRES Row Crop Tyre Selections lotation Tyre Selections	VF380/90R46, LSW480/70R46	VF380/90R46, LSW480/70R46	VF380/105R50, VF480/80R50		
YRES tow Crop Tyre Selections lotation Tyre Selections OLUTION SYSTEM	VF380/90R46, LSW480/70R46	VF380/90R46, LSW480/70R46	VF380/105R50, VF480/80R50		
YRES low Crop Tyre Selections lotation Tyre Selections OLUTION SYSTEM olution Tank Fill Connection/Capacity	VF380/90R46, LSW480/70R46 LSW	VF380/90R46, LSW480/70R46 680/50R46	VF380/105R50, VF480/80R50 LSW710/60R46		
YRES ow Crop Tyre Selections lotation Tyre Selections oLUTION SYSTEM olution Tank Fill Connection / Capacity olution Tank Material	VF380/90R46, LSW480/70R46 LSW	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 I tank	VF380/105R50, VF480/80R50 LSW710/60R46		
YRES ow Crop Tyre Selections lotation Tyre Selections OLUTION SYSTEM olution Tank Fill Connection / Capacity olution Tank Material olution Tank Fill Location	VF380/90R46, LSW480/70R46 LSW	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 I tank Stainless steel	VF380/105R50, VF480/80R50 LSW710/60R46		
YRES Row Crop Tyre Selections Iotation Tyre Selections OLUTION SYSTEM Solution Tank Fill Connection/Capacity Solution Tank Material Solution Tank Fill Location Rinse Tank Fill Connection/Capacity	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 I tank Stainless steel Service Center / Front Fill	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES OW Crop Tyre Selections OUTION SYSTEM Olution Tank Fill Connection/Capacity Olution Tank Material Olution Tank Fill Location inse Tank Fill Connection/Capacity inse Tank Fill Location	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 1680/50R46 76.2 mm 4,542 I tank Stainless steel Service Center / Front Fill 50.8 mm 530 I	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES OW Crop Tyre Selections OUTION SYSTEM Olution Tank Fill Connection/Capacity Olution Tank Material Olution Tank Fill Location inse Tank Fill Connection/Capacity inse Tank Fill Location THER TANKS AND CONTAINERS	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 1680/50R46 76.2 mm 4,542 I tank Stainless steel Service Center / Front Fill 50.8 mm 530 I	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES OW Crop Tyre Selections OUTION SYSTEM Olution Tank Fill Connection / Capacity Olution Tank Material Olution Tank Fill Location inse Tank Fill Connection / Capacity inse Tank Fill Location THER TANKS AND CONTAINERS roduct Pump	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 I tank Stainless steel Service Center / Front Fill 50.8 mm 530 I Service Center	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES OW Crop Tyre Selections OUTION SYSTEM Olution Tank Fill Connection / Capacity Olution Tank Material Olution Tank Fill Location inse Tank Fill Location THER TANKS AND CONTAINERS roduct Pump ence Row Nozzles	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 I tank Stainless steel Service Center / Front Fill 50.8 mm 530 I Service Center Hypro centrifugal pump, 50.8×38.1 mm, stainless steel housing	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES ow Crop Tyre Selections lotation Tyre Selections OLUTION SYSTEM olution Tank Fill Connection / Capacity olution Tank Material olution Tank Fill Location inse Tank Fill Connection / Capacity inse Tank Fill Location THER TANKS AND CONTAINERS roduct Pump ence Row Nozzles ODM	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 I tank Stainless steel Service Center / Front Fill 50.8 mm 530 I Service Center Hypro centrifugal pump, 50.8×38.1 mm, stainless steel housing	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES OW Crop Tyre Selections OUTION SYSTEM Olution Tank Fill Connection/Capacity Olution Tank Fill Connection/Capacity Olution Tank Fill Location inse Tank Fill Location THER TANKS AND CONTAINERS roduct Pump ence Row Nozzles ODM oom Length Selections	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 l tank Stainless steel Service Center / Front Fill 50.8 mm 530 l Service Center Hypro centrifugal pump, 50.8×38.1 mm, stainless steel housing Fixed 45 degree angle	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES Row Crop Tyre Selections Iotation Tyre Selections OLUTION SYSTEM Solution Tank Fill Connection/Capacity Solution Tank Material Solution Tank Fill Location Rinse Tank Fill Connection/Capacity Rinse Tank Fill Location Wither Tank Section Product Pump Gence Row Nozzles Boom Length Selections Boom Plumbing Material	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 l tank Stainless steel Service Center / Front Fill 50.8 mm 530 l Service Center Hypro centrifugal pump, 50.8×38.1 mm, stainless steel housing Fixed 45 degree angle 18.3/30.5 m, 18.3/27.4/36.6 m, 21.0/41.1 m model dependent	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
TYRES Row Crop Tyre Selections Flotation Tyre Selections Solution Tank Fill Connection/Capacity Solution Tank Material Solution Tank Fill Location Rinse Tank Fill Location Rinse Tank Fill Location DTHER TANKS AND CONTAINERS Product Pump Fence Row Nozzles BOOM Boom Length Selections Boom Nozzle Spacing	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 l tank Stainless steel Service Center / Front Fill 50.8 mm 530 l Service Center Hypro centrifugal pump, 50.8×38.1 mm, stainless steel housing Fixed 45 degree angle 18.3/30.5 m, 18.3/27.4/36.6 m, 21.0/41.1 m model dependent Stainless steel spray bars	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
YRES Row Crop Tyre Selections Flotation Tyre Selections Solution Tank Fill Connection/Capacity Solution Tank Material Solution Tank Fill Location Rinse Tank Fill Location Rinse Tank Fill Location Product Pump Ference Row Nozzles Boom Length Selections Boom Nozzle Spacing Boom Height Adjustment	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 l tank Stainless steel Service Center / Front Fill 50.8 mm 530 l Service Center Hypro centrifugal pump, 50.8×38.1 mm, stainless steel housing Fixed 45 degree angle 18.3/30.5 m, 18.3/27.4/36.6 m, 21.0/41.1 m model dependent Stainless steel spray bars 508 mm	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		
Speed Range(s) FYRES Row Crop Tyre Selections Interfact Selections Solution Tank Fill Connection / Capacity Solution Tank Fill Connection / Capacity Solution Tank Fill Location Rinse Tank Fill Location DTHER TANKS AND CONTAINERS Product Pump Fence Row Nozzles Soom Length Selections Soom Height Selections Soom Height Adjustment DVERALL DIMENSIONS FY Content Selections Soon Selections Soon Height Adjustment Sour Weight Sour Weight Sour Selections Sour Weight Sour Selections Sour Selections Sour Height Adjustment Sour Selections Sour Selections Sour Selections Sour Height Adjustment Sour Selections Sour Selections Sour Selections Sour Height Adjustment Sour Selections Sour Selections Sour Selections Sour Selections Sour Height Adjustment Sour Selections Sour	VF380/90R46, LSW480/70R46 LSW 76.2 mm 785 I tank	VF380/90R46, LSW480/70R46 680/50R46 76.2 mm 4,542 l tank Stainless steel Service Center / Front Fill 50.8 mm 530 l Service Center Hypro centrifugal pump, 50.8×38.1 mm, stainless steel housing Fixed 45 degree angle 18.3/30.5 m, 18.3/27.4/36.6 m, 21.0/41.1 m model dependent Stainless steel spray bars 508 mm	VF380/105R50, VF480/80R50 LSW710/60R46 76.2 mm 6,057l tank		



f in Caseih.com

A Free phone: 00 800 22 73 44 00

Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends AKCELA lubricants.

TP01 / SM / 09-22 / Printed in Austria - Cod.No. 22MEAC1002COMINB

