

AFS CONNECT QUADTRAC & STEIGER

AFS CONNECT QUADTRAC & STEIGER

TRACTORS FROM
475 – 715 hp



CASE IH

THE STRONGEST TRACTOR EVER... AGAIN

For over 60 years, Quadtrac® and Steiger® series tractors have helped producers like you get more from the job in demanding conditions. Now we are proud to launch our most powerful tractor ever, the new AFS Connect™ Quadtrac with 715 hp.

+11 %
more power

GREATER EFFICIENCY

With up to 778 hp maximum power

The concept behind the development of the Quadtrac 715 is not just more power. Our aim was to create a machine that matches the requirements of the largest farms: operating implements at their ideal speed to achieve greater working efficiency. Get your work done within those short windows of ideal weather, even in tough working conditions. And rest assured, your soil is protected: a larger footprint means fewer passes and even greater efficiency.



Model	Rated power ECE R120 ¹⁾ @ 2,200 rpm [kW/hp (CV)]	Maximum power ECE R120 ¹⁾ [kW/hp (CV)]	Transmission	Max. lift capacity [kg]	Max. pump flow Standard (Option) [l/min]
QUADTRAC 715	527 / 715	572 / 778	16F/2R PowerDrive	10,092	159 (216 or 428)
QUADTRAC 645	474 / 645	514 / 699	16F/2R PowerDrive	10,092	159 (216 or 428)
QUADTRAC 595	438 / 595	482 / 656	16F/2R PowerDrive	10,092	159 (216 or 428)
QUADTRAC 555	408 / 555	451 / 614	16F/2R PowerDrive	10,092	159 (216 or 428)
QUADTRAC 525 STEIGER 525	386 / 525	425 / 578	16F/2R PowerDrive or CVTDrive	10,092	159 (216 or 428)
STEIGER 475	349 / 475	384 / 522	16F/2R PowerDrive or CVTDrive	10,092	159 (216 or 428)

¹⁾ECE R120 corresponds to ISO 14396 and 97 / 68 / EC

+11 %
bigger fuel tank

+3%
larger footprint

+11%
more light output



IMPRESSIVE PERFORMANCE

- Powerful engine with up to 778 hp maximum power
- Up to 428 litres per minute flowrate for up to eight hydraulic remote valves
- Colossal rear lift capacity of 10,092 kg
- Up to 40 % torque rise for best engine response

CONNECTIVITY MEANS EFFICIENCY

- AFS Connect telematics solution – the gateway to Quadtrac AFS Connect™ series tractors
- Extended remote capabilities
- Manage and optimize your farm, fleet, and data with AFS Connect at any time
- Remote screen sharing

COMFORT AT THE HIGHEST LEVEL

- Intuitive AFS Vision Pro operating system featuring new AFS Pro 1200 monitor
- New intuitive and ergonomic controls developed with our customers
- Industry-leading configurable buttons can be programmed with over 100 functions

NEVER EQUALLED

- Articulated steering and Tri-Point Oscillation delivers full power
- Four-track design distributes weight evenly over a total footprint of 5.7 m²
- Oscillation of 26° is provided both upwards and downwards



f y i n i
caseih.com

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial Australia Pty Ltd reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used. 2024 CNH Industrial Australia Pty Ltd. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial Australia Pty Ltd, are the property of those respective companies Printed in Australia. www.caseih.com (Code: 24CIHAFSQUADTRACSPEC) July 2024

CASE IH