

FARMALL C

TRACTORS FROM
55 – 75 HP



THE FARMALL C 55-75 HP RANGE

Compact and versatile

3.4 l
common rail diesel
engine

Case IH Farmall C tractors define versatility, with a compact design concealing an engine and transmission that punch way above their weight. That's the secret to their ability to switch easily between yard jobs in confined spaces one moment and putting in a full day's field work the next.

POWERFUL AND EFFICIENT

Despite its compact stature, the Farmall C is engineered to deliver robust performance and exceptional efficiency, ensuring every task is completed with ease.

AGILE AND ADAPTABLE

With its low construction height of 2,420 mm, the Farmall C effortlessly maneuvers within farm buildings and tight spaces, making it your ideal choice for versatile farm operations.

LIGHTWEIGHT YET CAPABLE

Weighing in at 2,800 kg and boasting a remarkable turning circle of 3.75 m, this tractor is both nimble and reliable, ready to tackle a wide range of agricultural tasks.

CABIN COMFORT

Experience a comfortable and ergonomic cabin that enhances your productivity and reduces operator fatigue.

EFFORTLESS MAINTENANCE

Benefit from a one-piece bonnet design and 600 h service intervals that simplifies maintenance tasks, keeping your Farmall C running smoothly.

90 l
fuel tank capacity



COMFORT

- Stay comfortable throughout the day with natural ventilation via openable windows or opt for air conditioning to maintain a fresh interior
- Access the cab effortlessly with wide steps and a one-piece door design
- Regardless of weather conditions, superb visibility is assured, thanks to the A-pillar exhaust and instrumentation mounted on the steering column
- Illuminate your surroundings with a selection of lighting packages that can transform night into day
- Boost your productivity with easy-to-read instrumentation

4
cylinders

ENGINE

- 4-cylinder, 3.4 l Common Rail Diesel engine with wastegate turbocharger
- Extend your working hours with a generous 90-liter fuel tank capacity
- Simplify maintenance tasks with a one-piece bonnet design

3.75 m
turning radius

PERFORMANCE

- **Fast cycle times:** Seamlessly control your front loader with the integrated joystick, ensuring efficient and user-friendly handling
- **Compact design:** With a low construction height of just 2,420 mm, the Farmall C is perfectly suited for tasks within the yard or farm buildings, maximizing its versatility

HYDRAULICS


- **Solid lifting capability:** Benefit from a robust lifting capacity of up to 2,500 kg, providing you with reliable strength for various tasks on the farmyard
- Benefit from up to 3 mechanical remote valves at the rear
- Precise control over rear linkage with Mechanical Hitch Control (MHC)
- Explore the loader-ready factory option for a seamlessly integrated design that ensures compatibility with Case IH L-loaders

REMARKABLY MANOEUVRABLE AND SAFE

- **Nimble and lightweight:** At a mass of 2,800 kg and a tight turning radius of 3.75 m, the Farmall C combines lightness and manoeuvrability to tackle various tasks with ease
- **Off-road excellence:** Equipped with all-wheel drive and differential lock, the Farmall C excels in challenging terrain, providing the traction and performance needed for demanding agricultural environments.



   
caseih.com

 Free phone: 00 800 22 73 44 00

Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **AKCELA** lubricants.

TP01 / SM / 12/2023 / Printed in Austria - Cod.No. 23C0020COMINB

CASE IH