

FARMALL® COMPACT 25A

SPECIFICATIONS



MODEL	25A
<i>SERIES CLASSIFICATION</i>	<i>STANDARD</i>
Operator Station	Non-Cab
Traction	MFD
ENGINE	
Type	3-cylinder, Tier 4 B/Final
Displacement	1.3 L (80.4 cu. in.)
Engine HP*	24.6
PTO HP*	19.2
Rated Engine RPM	2,500
TRANSMISSION / PTO	
Standard	12 × 12 Mechanical shuttle with synchro shift (dry clutch)
Optional	Hydrostatic
Differential Lock	Mechanical
MFD Engagement	Independent Electrohydraulic
PTO Speed (Standard / Optional Mid-PTO)	540 / 2,000
AXLES	
Front	Mechanical Front Drive (MFD)
Rear	Inboard planetary
HYDRAULICS / HITCH	
Type	Open Center
Rear Remotes (Standard / Optional)	0 / 1 DIA
Implement Pump / Flow*	7.9 gpm
3-point Hitch Category and Draft Sensing Type	Cat. 1 / N/A
Lower Link End / Stabilizer Type	Fixed / Telescopic Stabilizers
Standard Lift Capacity @ 24 in. Behind Pin (Standard / Optional)	1,433 lb. (650 kg)
CAPACITIES	
Fuel Tank (Cab / Non-Cab)	N/A / 7.4 gal
Diesel Exhaust Fluid Tank	No DEF required
DIMENSIONS & WEIGHTS	
Wheelbase (2WD / MFD)	N/A / 65.9 in. (1 674 mm)
Overall Length (2WD / MFD)	N/A / 117.2 in. (2 976 mm)
Minimum Height (ROPS Folded)**	68.2 in.
Overall Height MFD (Top of Cab / ROPS)	N/A / 88.2 in. (2 241 mm)
Weight w/o Ballast (Cab / Non-cab 2WD)	N/A
Weight w/o Ballast (Cab / Non-cab MFD)	N/A / 2,469 lb. (1 120 kg)

*At rated engine RPM. **With R4 tires

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2023 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH23062102

